Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-013:
Expires: March 31 1993

Second Second Company Second Seco	Do not use this form for proposals to drill not deepen or reentry to a different reservoir. Submit in training to the deepen or reentry to a different reservoir.	BUREAU OI	F LAND MANAGEMENT	5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to eather the definition of the Name Submitt in triple of the Name Submitt in triple of the Name Submitt in triple of the Name Submitt in triple of the Name Submitt in triple of the Name Submitt in triple of the Name Name of Operator Roddy Production Company Roddy Ro	Do not use this form for proposals to drill or to deepen or reentry to additional reservoir. Submit in trial or CA. Agreement Designation	SHADDA NOTICE	S AND DEPORTS ON WELL O	2: U I NM010063
Submit in Triplicate 7. If Unit or CA. Agreement Designation 7. If	Submit In Triplicate 1. If the or CA. Agreemen Designation 1. If the or CA. Agre			6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE 7. If Unit or CA. Agreement Designation 8. Well Sume and No. 8. Well Name and No. 8. Well Name and No. 8. All Well No. 9. API Well No. 10. API Well No. 10. API Well	SUBMIT IN TRIPLICATE 7. If Unit or CA. Agreement Designation 8. Well Name and Ro. Lucertne Federal No. 4 Lucertne Federal No. 4 Lucertne Federal No. 4 Andress and Telephone No. P.O. Box 2221, Farmfungton, New Mexico 87499, 505-325-5220 10. Field and Pool, or Exploretry Area Mest Rucy Pictured Cliffs 11. County or Parish, State CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Softwagers Repon Filed Abandonment Notice Softwagers Repon Prized Abandonment Notice Softwagers Repon Describe Proposed or Compised Operations (Charity state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directocally drilled. give substrates focations and measured and the vertical depths for all markers and zones pertinent to flaw work.)* Sput 3 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf., 3-55, LTRC cassing with cement nones quicke shoe and 7"Kts 3/4" bow sporting cemental layers at 57°, 186°, and 208'. Cassing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% Cacl1 through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 pSi for 15 minutes on 11/19/94. I hereby ceriff, Base to feeture of state office use) Complete Propagage, a market correct Tale Agent Describe Federal or state office use) Complete Propagage, a market correct Tale Agent Describe Federal or state office use) Complete Propagage, a market correct Tale Agent Describe Federal Reports, if any: NOV 2 1994	Use "APPLICATION F	OR PERMIT—" for such proposals	1 YOU : 1
Type of Well	Type of Well			7. If Unit or CA. Agreement Designation
Second Second Company Second Seco	Supering	SUBM	IT IN TRIPLICATE	7. If our of CA, Agreement Designation
Name of Operators Roddy Production Company Address and Telephone No. 4 P.O. Box 2221, Parmington, New Mexico 87499, 505-325-5220 10. Field and Pool, or Exploratory Area Nest Ktuzz Pictured Cliffs 11. County or Parish, State 11. County or Parish, State 11. County or Parish, State San Juan County, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Noice of Intent Subsequent Report Final Abandonnent Notice Recompletion Plagging Back Altering Casing Other Other Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting may proposed work. If well is directionally drilled, give substanface locations and measured and true vertical depths for all markers and zonce pertinent to this work.)* Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LTBC casing with cement nose guide shoe and 7"X8 3/4" bow spiring centralizers at 5", 186', and 208'. Casing set at 230 feet KB. Cement with 60 scakes (70.8 st f) class B with 28 Cacil and 1/4/4/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) class B with 28 Cacil and 1/4/4/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) class B with 28 Cacil and 1/4/4/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (70.8 st B) with 28 Cacil and 1/4/4/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (70.8 st B) with 28 Cacil and 1/4/4/sk celloflake. Did not circulate cement of sacrofice use Nov 3 0 1994 Nov 3 0 1994	Name of Operators Roddy Production Company Address and Telephone No. P.O. Box 2221, Farmington, New Mexico 87499, 505-325-5220 10. Field and Pool, or Epiperatory Area Location of Well Organy, Sec. T. R. M. or Survey Description) 1765' FNL - 790' FWL 2 / - 2 y N - CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Notice of Intern Notice of Intern Subsequent Report Final Abandonment Notice Abandonment Notice Describe Proposed or Completed Operations (Citarly state all pertitions details, and give pertitions dates, including estimated date of starting any proposed work. If well in directionally dolled. Spud 8 3/4" Surface hole at 12:15 FM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LiT&C casting with cement nose guide shoe and 7"X8 3/4" bow spiring centralizers at 57', 186', and 208'. Casting set at 230 feet KB. Cement with 60 sacks (70.8 cf) class B with 2% Cacll and 1/4/4/s celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (50 cf) class B with 2% Cacll and 1/4/4/s celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (50 cf) class B with 2% Cacll and 1/4/4/s celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (50 cf) class B with 2% Cacll through 1". Circulated 2 1/4 bbls. good Shurry to surface. Job completed at 7:00 PM, 11/18/94. Wor 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. NOW 3 0 1994 Only 2 1994	1. Type of Well		
Roddy Production Company Address and Telephone No. 30-045-2916 10-Pital and Production (New Mexico 87499, 505-325-5220 10-Pital and Prod. or Exploratory Area Nest Kutz Pictured Cliffs	Roddy Production Company Addies and Telephone No. 30-045-29162 10. Feld and No. 4 by AR Well No. 30-045-29162 10. Feld and No. 4 by Description (Foodge, Sec., T. R. M. or Survey Description) 1765' FNL - 790' FWL 2 / - 2 y y - 1 y CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Note of Intent Nother of Intent Note of Intent Nother of Intent Nother of		···	8. Well Name and No.
Address and Telephone No. P.O. Box 2221, Farmington, New Mexico 87499, 505-325-5220 Do-045-29162 Do-045-29	Address and Telephone No. P.O. Box 2221, Farmington, New Mexico 87499, 505-325-5220 The field and Poly, or Exploratory Area (Mexico 1974) Tree of Submission Type of Action Noisce of Intent Subsequent Report Final Abandonment Notice Describe Proposed or Completed Operations (Clearly state all pertinent datas), secularly substitutes locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215,14 feet of 7", 23 ppf, 7.–55, LTRC cassing with cement noise guide shoe and 7"X8 3/4" bow spring central izers at 57', 186', and 208'. Cassing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 28 Cacl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 28 Cacl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 28 Cacl Through I". Circulated 2 1/4 bibls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WCC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. How 3 0 1994 Title Agent Describe the pipe of the pipe	•		
P.O. Box 2221, Farmington, New Mexico 87499, 505-325-5220 International Content	P.O. Box 2221, Farmington, New Mexico 87499, 505-325-5220 To Field and Pool, or Despiratory Area (Decision of Well (Foodge, Sec. T. R. M. or Survey Description) West Kutz Pictured Cliffs 1765' FNL - 790' FWL 2 / - 2 y // - // / San Juan Country, New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Novice of Intern Subsequent Report Plugging Back Incompletion New Constraints	Roddy Production Company 3 Address and Telephone No.		
Contained of Well (Footage, Sec., T. R. M., or Survey Description) Neet Kutz Pictured Cliffs	Location of Well (Footage, Sec., T. R. M., or Survey Description) West Kutz Pictured Cliffs	·	Now Marian 97400 FAE 225 F220	
1765' FNIL - 790' FWIL 2 - 2 y/V	The control of Prints State Check Appropriate Box(s) to Indicate Nature of Notice, Report, or Other Data Type of Submission	Location of Well (Footage, Sec., T., R., M., or Survey	Description)	
San Juan County, New Mexic CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Notice of Intern Notice of Internation	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Notice of Intern Notice of Intern Subsequent Report Final Abandonment Notice Casing Repair Other Countriction Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"x8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% Cacl and 1/4/s/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% Cacl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WCC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Tide Agent Date NOV 3 0 1994 NOV 3 2 1994	·	•	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	1765' FNL - 790' FWL	21 - 28N-1/W	To some state of the state of t
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent			San Juan County, New Mexic
TYPE OF SUBMISSION Notice of Intern	TYPE OF SUBMISSION Notice of Intent	CHECK APPROPRIATE BOX	X(s) TO INDICATE NATURE OF NOTICE R	
Notice of Intent Notice of Intent Recompletion New Construction New Construction Non-Routine Fracturing Water Shut-Off Casing Repair Water Shut-Off Change Water Shut-Off Ch	Notice of Inters			
Subsequent Report	Subsequent Report	THE OF SUBMISSION	TYPE OF AC	CTION
Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"x8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". (Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WCC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Pluging Back Water Shu-Off Water Sh	Subsequent Report	Notice of Intent	Abandonment	Change of Plans
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C cassing with cement nose guide shoe and 7"x8 3/4" bow spring centralizers at 57', 186', and 208'. Cassing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Tide Agent Date Conditions of approval, if any: NACCO NOV 2 2 1994	Casing Repair Casing Repair Casing Casing Conversion to Injection Conversion Conversi	V	Recompletion	New Construction
Final Abandonment Notice	Final Abandonment Notice	Subsequent Report		Non-Routine Fracturing
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WCC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Dispose Water (Nove: Reportable of sunding estimated date of starting any proposed work. If well is directionally drilled. Dispose Water (Nove: Report sund proposed work.)*	Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WCC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Date 11/21/94	Π		Water Shut-Off
Conditions by approval, if any: Close Report rough control to Multiple completion on well completed Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled.	Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C cassing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch time pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. I hereby certify thus the forgoing is truyland correct Signed Table Agent Date 11/21/94 Chis space for Federal or State office use) Approved by	Final Abandonment Notice		
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"x8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk cellofilake. Did not circulate cement. Run 1 inch time pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Diff	Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Tide Agent Date 11/21/94 CCEPTED FOR RECORD Date Conditions of approval, if any: NOV 3 2 1994		C Other	
Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Did Good Div 5 Signed Div 6 Div 6 Div 7 Div 7	Spud 8 3/4" surface hole at 12:15 PM, 11/18/94. Drill to 235'. Ran 215.14 feet of 7", 23 ppf, J-55, LT&C casing with cement nose guide shoe and 7"X8 3/4" bow spring centralizers at 57', 186', and 208'. Casing set at 230 feet KB. Cement with 60 sacks (70.8 cf) Class B with 2% CaCl and 1/4#/sk celloflake. Did not circulate cement. Run 1 inch tine pipe in annulus. Tag cement at 38 feet. Pump 50 sacks (59 cf) Class B with 2% CaCl through 1". Circulated 2 1/4 bbls. good slurry to surface. Job completed at 7:00 PM, 11/18/94. WOC 12 hours. Pressure test BOPE and surface casing to 600 psi for 15 minutes on 11/19/94. Held okay. Diff Carl Spring Policy	Describe Proposed or Completed Operations (Clearly state	all pertinent details and give pertinent dates including actional dates	Completion or Recompletion Report and Los form)
Title Agent Date 11/21/94	Title Agent Title Agent OCEPTED FOR RECORD Approved by Conditions of approval, if any: NMOCO Title Agent NMOCO NOV 2 2 1994	spring centralizers at 57', with 60 sacks (70.8 cf) Class circulate cement. Run 1 inc 50 sacks (59 cf) Class B with slurry to surface. Job comp	186', and 208'. Casing set at 230 ss B with 2% CaCl and 1/4#/sk celloch time pipe in annulus. Tag cement th 2% CaCl through 1". Circulated 20 celeted at 7:00 PM, 11/18/94. WOC 12	feet KB. Cement flake. Did not t at 38 feet. Pump 2 1/4 bbls. good 2 hours. s on 11/19/94.
(This space for Federal or State office use) Approved by Title Date NOV 2 = 1994	(This space for Federal or State office use) Approved by Title Date NOV 2 = 1994	. I hereby certify that the foregoing is true and correct		
Approved by Title Date Conditions of approval, if any: NMOCD NOV 2 0 1994	Approved by Title Date NMOCD NOV 2 = 1994	Signed V9. E. Fielde	Title Agent	Date 11/21/94
Conditions of approval, if any: NOV 2 2 1994	Conditions of approval, if any: NOV 2 = 1994			GCEPTED FOR RECORD
The state of the s	Milit S . 1994			
18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any decrement of the Visit of Section 1001.	e 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States and Tribe Destrict Statements epresentations as to any matter within its jurisdiction.		• ••••••••	NOV 2 ↑ 1994
	epresentations as to any matter within its jurisdiction.	e 18 U.S.C. Section 1001 makes it a crime for any person	n knowingly and willfully to make to say decomposite of the	United States and falls of the State of APPLAP

DV