

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1710' FNL, 855' FEL Sec. 7, T-29-N, R-7-W, NMPM

5. Lease Number
SF-78943
If Indian, All. or
Tribe Name
Agreement Name
San Juan 29-7 Unit
Well Name & Number
San Juan 29-7 U 52
API Well No.
30-039-54604
Field and Pool
Blanco Mesa Verde
County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action	
☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injectio
	☒ Other - pay add	

13. Describe Proposed or Completed Operations

04-26-94 MOL&RU. Blow down. ND WH. NU BOP. TOO H w/tbg. Ran scraper to 5116'. Set CIBP @ 5100'.
04-27-94 Set FBP @ 4810'. PT CIBP 3000#/15 min, ok. Set pkr @ 4640'. PT csg 1000#/15 min, ok. TOO H w/FBP.
Ran GR-CBL-CCL 5100-4600'. Perf Menefee 4832-5063' w/2 spf. Set FBP @ 4818'. Spot 2000 gal acid.
Frac Menefee w/26,250# 40/70 sand, 200,000# 20/40 sand and 72,324 gal x-link gel.
04-28-94 TOO H w/tbg & FBP. TIH to 4856'. Blow down.
04-29-94 Blow well.
04-30-94 Set FBP @ 4818'. Set RBP @ 4630'. Dump 2 sx sand. Load hole w/ 90 BW. PT 3000#/15 min, ok. Ran CBL-GR-CCL 4630-2900'. TOC @ 4065'. Perf 3 holes @ 3933'. Well on vacuum. Shot 2 holes @ 3650'. Set cmt ret @ 3887'. Est inj rate. Spot 100 sx CI "B" w/2% CaCl2. Left 1 bbl cmt on top of ret. WOC.
05-01-94 Set pkr @ 3354'. Est inj rate. Spot 100 sx Class "B" w/2% calcium chloride, Displace w/15 BW. Left 3 bbl cmt in csg. Release pkr. Pull up to 3228'. Reverse out 26 BW. Reset pkr. TIH, tag TOC @ 3388'. Drl cmt 3388-3483'. Drl cmt 3483-3543'.
05-02-94 Drl cmt 3543-3675'. PT csg 700#/15 min, ok. Tag TOC @ 3836'. Drl cmt & ret. TOO H. Ran CBL-GR-CCL. TOC @ 3626'. Perf Lewis 3933-4603'. Set FBP @ 3697'. Spot 2000 gal acid. Set pkr @ 3697'.
05-03-94 Frac Lewis w/105,000# 20/40 sand and 45,000 gal gel. Blow down.
05-04/05 Blow well. TOO H w/RBP. TIH, CO to CIBP. Blow well. Drill on CIBP @ 5100'.
05-06-94 Drill CIBP @ 5100'. CO to 5320'. TOO H. TIH, blow w/gas.
05-07-94 Blow well. Ran 167 jts 2 3/8", 4.7#, J-55 tbg landed @ 5278'. Released rig.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 5/9/94

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

MAY 19 1994

Date

Signature of Approving Official