

Subml. 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24604
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 29-5 Unit
8. Well No. 213
9. Pool name or Wildcat Basin Fruitland Coal Gas

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 300 W. Arrington, Ste. 200, Farmington, NM 87401	
4. Well Location Unit Letter M : 1165 Feet From The South Line and 1145 Feet From The West Line Section 22 Township 29N Range 5W NMPM Rio Arriba County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6693' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: OIL CON. DI' ☐ RECEIVED APR 26 1990 DIST. 2	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☐ OTHER: Set liner & complete ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-22-90: Schlumberger ran CBL from 1000'-180'. TOC at 340'. Pressure tested casing and BOP & ground equipment to 2500 psi for 30 min. Tagged TOC at 3340' pressure tested all pipe rams, blooie line valves with choke valves to 2500 psi-OK.

2-26-90: Ran LDT, GR-CNL, Microlog, NGT. Set 15.5# J-55 LTC 5-1/2" liner @ 3664' w/50 sx Class "B" Neat w/2% CaCl2. Top of liner @ 3286'.

3-13-90: Drld out cement to 3650'. Ran GR-CCL-CBL from 3650'-2500', TOC at 3530' w/100% bond, 50-95% bond across Ojo Alamo, pressure tested casing and BOP to 3900 psi for 30 min - OK.

3-14-90: Perf'd Fruitland Coal intervals from 3460'-3644'. Total of 63' 2/2SPF. Frac'd w/136,000 gals 30-55 Linier gel w/1% KCl w/19,000# 40/70 and 183,000# 12/20 sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. L. Maples TITLE Reg. & Pro. Assistant DATE 4/25/90

TYPE OR PRINT NAME J. L. Maples TELEPHONE NO. 367-1411

(This space for State Use)

Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT 1 DATE APR 26 1990

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

3-17-90: Set 2-7/8" J-55 8rd EUE 6.4#/ft tbg in hanger, set @ 3630'
w/expendable check @ 3634', SN @ 3603'.

3-17-90
J-55 8rd EUE
6.4#/ft tbg
set @ 3630'
w/expendable check
@ 3634'
SN @ 3603'