				`	
Form 9-331 (May 1963)	UNITED STATES SUBMIT IN TRIPLICATE.  DEPARTMENT OF THE INTERIOR (Other instructions on re-				roved.
(May 1805)				5. LEASE DESIGNAT	ON AND SERIAL NO.
	GEOLOGICAL SURVEY			SF 078415A	
	SUNDRY NOTICES	AND REPORTS	ON WELLS	6. IF INDIAN, ALLO	TEE OR TRIBE NAME
			back to a different reservoir.		
1.				7. UNIT AGREEMENT	NAME
	ELL X OTHER				
2. NAME OF OPERATOR				8. FARM OR LEASE Lively	NAME
	PLORATION COM				
		Engr. & Prod.		9. WELL NO.	
4. LOCATION OF WE See also space 1	LL (Report location clearly	ton, New Mexic	CO 87401 State requirements.	3 E 10. FIELD AND POOL	
	.790'FNL, 800'	FINT		Basin Dako	OR BLK. AND
_	.750 INII, 000	Sec. 9-T29	BEA		
				N.N	1.P.M.
14. PERMIT NO.	ŀ	ELEVATIONS (Show whether D	F, RT, GR, etc.)	12. COUNTY OR PAR	ISH 13. STATE
		6435'GL		San Juan	N.M.
16.	Check Approp	oriate Box To Indicate 1	Nature of Notice, Report, or (	Other Data	1
	NOTICE OF INTENTION	ro:	SUBSEC	Unit Pear or:	
TEST WATER S	AUT-OFF PULL	OR ALTER CASING	WATER SHUT-OFF	REPAIRIN	o wall
FRACTURE TREA	T MULTI	PLE COMPLETE	FRACTURE TREATMENT	REPAIRIN	CASING S
SHOOT OR ACID	IZE ABAND	ои*	SHOOTING OR ACIDIZING	OIL COMMON	MENT*
REPAIR WELL	CHANG	E PLANS	(Other)	a of Autorit is Tana	n on Well
(Other)				s of multiple complete pletion Report and Log	
proposed wor nent to this w	ED OR COMPLETED OPERATION k. If well is directionally ork.) *	NS (Clearly state all pertine drilled, give subsurface loce	nt details, and give pertinent dates tions and measured and true vertic	s, including estimated cal depths for all mark	Tate of starting any ters and zones perti-
12/22/80	Spud Well				
12/22/80	T.D. 275'.	Ran 6 joints 9	9-5/8", 36.0 lb.,	K-55 casing	(254')
			: Class "B" cement ele per sack. Ceme		
			th 500 psig. Tes		ed to
		obbuild debt wi	101 200 p <b>31</b> 9. 102	C OK.	
12/28/80	T.D. 3640'.	Ran 88 joints	of 7", 23.0 lb.,	K-55 casin	g (3644.94')
	set at 3640'	with 400 sack	s Howco Light 12%	Gel with 6	-1/4 lbs.
	Gilsonite pe	r sack, and 10	00 sacks regular 2	% calcium c	hloride.
1/1/81	m n 7575!	Dan 105 jaint	~ 4 1 /2 U 10 E0 c	11 60 11	77 FF
1/1/01	set at 7569'	with 380 gack	4-1/2", $10.50$ & $50/50$ Pozmix (2)	: 11.60 lD., '9 Col) with	K-55 casing
			d-9 & 7/10% CFR-2		1 0-1/4
				r	
	ELY EXPLORATION				
18. I hereby certify	that the foreokigiNAL	SIGNED BY Pr	esident, Walsh En	gr.	1 /7 /01
SIGNED	EWFLI N	WALSH TITLE &	Prod. Corp.	•	1/7/81
(This space for	ll N. Walsh, I Federal or State office use	)		<del></del>	
		•			

DATE \_\_\_

APPROVED BY \_\_\_\_\_\_\_ CONDITIONS OF APPROVAL, IF ANY: