

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well  
2. NAME OF OPERATOR  
Tenneco Oil Company  
3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1050' FSL & 1050' FEL "P"  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

(other) Commence Drilling operations

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5/17/81. MIRURT. Spud well 5/16/81 w/Four Corners rig #7. Drill 12-1/4" hole. Circ. and cond. (depth 257') RU and run 6 jts (245) of 9-5/8" 36# K-55 STC csg set @ 256'. Cmt w/250 sx Class B w/2% CACL<sub>2</sub> and .4% Flocele. Plug down. Circ cmt to surface. WOC. NU BOPS. Pressure test to 1000 PSI for 30 mins. Drill cmt. Drilled out and ahead.

5/20/81. Drill to 3685' 5/19/81. Short trip, circ and cond hole. Laid down drill pipe and collars. Run 80 jts. 7" 23# csg K-55 STC. Shoe @ 3684'. Cmt w/580 sx Class B w/2% CACL<sub>2</sub>. Displaced 40 bbls of 145 bbls. Pump lost prime. Regained prime 20 mins later. Could not move cmt. Max pressure: 2200 PSI. RD National. Set slips, cut csg. RIH w/tooth bit. Tag top of cmt @ 940'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles W. Mott TITLE Div. Asst. Adm. Mgr. DATE 5-27-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

JUN 14 1981  
BY Dean Elliott