Form approved. Budget Bureau No. 1004-0135 UNITED STATES Form 3160-5 SUBMIT IN TRIPLICATE. Expires August 31, 1985 DEPARTMENT OF THE INTERIOR (Other Instructions verse side) (November 1983) 5. LEASE DESIGNATION AND SERIAL NO. (Formerly 9-331) BUREAU OF LAND MANAGEMENT SF-078415A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

"Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME GAS WELL WELL OTHER S PARM OR LEASE MAMP NAME OF OPERATOR Roelofs A Meridian Oil Inc. 9. WELL NO. 3 ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499 200 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. 10. FIELD AND POOL, OR WILDCAT See also space 17 below. At surface 7 790'S, 1655'W Basin Fruitland Coal 11. SSC., T., B., M., OR SLK. AND SURVEY OR AREA Sec. 10, T-29-N, R-08-W N.M.P.M. 15. BLEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH | 13. STATE 14. PERMIT NO. 6362 GL San Juan MM 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data AURESQUENT REPORT OF : NOTICE OF INTENTION TO: PELL OR ALTER CISING WATER SHUT-OFF ESPAIRING WELL TEST WATER SHUT-OFF ALTERING CASING FRACTURE TREAT MULTIPLE COMPLETE PRACTURE TREATMENT SHOOT OR ACIDIZE SHOOTING OR ACIDIZING Spud Well REPAIR WELL CHANGE PLANS (Norz: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) Othern 17 DESTRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and somes pertinent to this work.) Spudded well at 11:15 pm 11-28-88. Drilled to 236'. 11-28-88 jts. 9 5/8", 32.3#, H-40 surface casing set at 236'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (118 cu.ft.). circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok. TD 3045'. Ran 72 jts. 7", 20.0#, K-55 intermediate casing, 12-03-88 3034' set @ 3045'. Cemented with 30 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/ sx (907 cu.ft.), followed by 100 sx. Class "B" with 2% calcium chloride (118 cu.ft.) followed by 360 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/ sx (695 cu.ft.), followed by 100 sx. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min. Circulated to surface. LD L 18. I hereby certify that the foregoing is true and correct

*See Instructions on Reverse Side

TITLE Regulatory

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

FASHED 27

DATE

12-04-88

TITLE .