

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED
BLM

WELL ☐ GAS ☒ OTHER ☐

NAME OF OPERATOR

McKenzie Methane Corporation

ADDRESS OF OPERATOR

1911 Main Ave., #255, Durango, Colorado 81301

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1515' FSL, 965' FWL

API 30-045-28440

6422 GR

5. LEASE DESIGNATION AND SERIAL NO.

SF-078049

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hughes 27 L

9. WELL NO.

#5

10. FIELD AND POOL, OR WILDCAT

Basin FT Coal

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec27-T29N-R8W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRAC TURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRAC TURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Drilling Report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

SEE ATTACHED

RECEIVED
JUN 21 1991
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Ag Sage / CJ

TITLE Operations Manager

DATE 6/3/91

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 26 1991

*See Instructions on Reverse Side

NMOCB

FARMINGTON RESOURCE AREA

**MCKENZIE METHANE CORPORATION
DAILY DRILLING REPORT
Durango, Colorado**

11-29-90 Hughes 27 L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Running csg DEPTH: 263'
DAILY: MIRU 4 States Drilling. Drill mouse & rat hole.
Spud 12-1/4" hole @ 9:30 P.M. 11/28/90. Drill to 263'
w/ bit #1. TOOH. R/U & run 6 jts (240'), 8-5/8", 24#,
K55 STC csg set @ 252'. MUD: spud Surveys: N/A

11-30-90 Hughes 27L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Drlg DEPTH: 749'
DAILY: Finish running 8-5/8" csg. Cmt w/ 200 sx ClassB
+2% CaCl + 1/4#/sx cellophane flakes. PD @ 9:30 AM
11-29-90. Circ 14 bbl cmt to surf. WOC. NUBOP & test
same. Drl 7-7/8" hole @ 1:45 AM 11-30-90.
MUD: Benex & water. Surveys: 263' - 0. (Rerun)

12-1-90 Hughes 27L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Drlg DEPTH: 1415'
DAILY: Drill to 1382'. TFB #2. TIH w/ bit #3 & drill
to 1415'. MUD: Benex & water. Surveys: 820' - 2-1/4,
1193' - 2-3/4, 1382' - 2-1/2.

12-2-90 Hughes 27L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Drlg DEPTH: 2222'
DAILY: Drlg. TOOH w/ bit #3. TIH w/ bit #4.
MUD: Benex & water. MW: 8.7 Vis: 34
Surveys: 1661' - 1, 2158' - 1-1/2.

12-3-90 Hughes 27L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Drlg DEPTH: 2673'
DAILY: Drlg. TOOH w/ bit #4. TIH w/ bit #5.
MW: 8.8 Vis: 28
Surveys: 2386' - 2-3/4.

MCKENZIE METHANE CORPORATION
DAILY DRILLING REPORT
Durango Office

12-4-90

Hughes 27L #5

SW/4 Sec27-T29-R8, San Juan Co., NM

AART: TIH DEPTH: 3060'

DAILY: Drlg. TOOH w/ bit #5. TIH w/ bit #6. Drlg from
2998' to 3060'. TD @ 1:00 AM 12-4-90. Circ & cond hole
TOOH. Rig up Halliburton Wireline. First log on bottom
@ 2:30 AM. Ran openhole logs. TIH w/drill collars.

MW: 9.2 Vis: 42 Surveys: 3060' - 2-3/4.

MCKENZIE METHANE CORPORATION
DAILY DRILLING REPORT
Durango Office

12-5-90

Hughes 27L #5
SW/4 Sec27-T29-R8, San Juan Co., NM
AART: Waiting on completion. DEPTH: 3060'
DAILY: TTH w/ drill pipe. RU & LDDP & drl collars.
Ran 71 jts of 4-1/2", K55, 11.6# LTC csg @ 3049 KB.
Float collar @ 3011.44 KB. Cmt 4-1/2" csg w/ 500 sx
65/35 POZ + 1/4#/sx cellophane + 6% gel, followed by
180 sx 50/50 POZ + 2% gel + 1/4#/sx cellophane. PD @
4:00 PM 12-4-90. RR @ 4:00 PM. Circ approx 30 bbl cmt
to surf. MUD: N/A Surveys: N/A