

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SV 074132  
Unit A. L. Elliott "D"

SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |          |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |          |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |          |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |          |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 | <b>X</b> |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |          |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

A. L. Elliott "D" Farmington, New Mexico July 17, 1950

Well No. 3 is located 1850 ft. from [N] line and 1450 ft. from [E] line of sec. 12


NW 1/4 of Section 12 T-29-N R-9-W N.H.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Blanco-Pictured Cliffs San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6001 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

A. L. Elliott "D" Well No. 3. Spotted 110 gallons 15% MCA on bottom and loaded hole with water. Perforated Pictured Cliffs with 2 shots per foot 2640-2678. Sand-water fractured with 30,000 gallons water and 40,000 pounds sand. Formation broke at 1500 pounds. Average injection rate 60 barrels per minute. Completed as shut-in Blanco-Pictured Cliffs field development gas well July 15, 1950. Preliminary test 1947 MCPS, Pitot Tube Measurement.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

ORIGINAL SIGNED BY  
D. J. SCOTT

By \_\_\_\_\_


Title Field Clerk



**LTR**



**Job separation sheet**



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4  
Approval expires 12-31-60.

Land Office **Santa Fe**  
Lease No. **ST 070132**  
Unit **A. L. Elliott "D"**

SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |
|---|---|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**A. L. Elliott "D"** **Farmington, New Mexico** **July 17**, 19**58**  
Well No. **3** is located **1890** ft. from **[N]** line and **1490** ft. from **[E]** line of sec. **12**  
**SW/4 of Section 12** **T-29-N** **R-9-E** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Blanco-Pictured Cliffs** **San Juan** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6001** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)  
**A. L. Elliott "D" Well No. 3. On July 5, 1958, 5-1/2" casing was set at 2695' with 500 sacks 65 gal cement followed by 25 sacks neat cement. Casing and water shut-off were tested with 2600 pounds pressure, which held with no drop in pressure.**



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Pan American Petroleum Corporation**

Address **Box 127**

**Farmington, New Mexico**

ORIGINAL SIGNED BY  
**D. J. SCOTT**

By \_\_\_\_\_  
Title **Field Clerk**