

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SF 076337

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

W. D. Heath "A"

9. WELL NO.

2A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

NE/4 SE/4 Section 12

T-29-N, R-9-W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

AMCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1450' FSL x 870' FLL, Section 12, T-29-N, R-9-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5673' GL, 5686' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☒ Spud & Set Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

Spudded 13-3/4" hole on 11/5/77. Drilled to 261'. Set 9-5/8" 32.3# H-40 casing at 260' with 340 sx Class "B", 6% gel, 2% CaCl₂. Circulated 10 bbls. good cement. Pres-
sured up to 800 psi; held OK.

Drilled 8-3/4" hole to 2540'. Set 7" 20# K-55 casing at 2540 with 440 sx Class "B", 6% gel, 2 lbs. medium Tuf Plug per sx. Tailed in with 100 sx Class "B", 2% CaCl₂.

Drilled 6-1/4" hole to a total depth of 4648'. The 4-1/2" 11.6# K-55 casing liner was set from 2322 to 4648' with 200 sx Class "B" 50:50 Poz, 6% gel, 2 lbs. medium Tuf Plug per sx, 0.2% friction reducer. Tailed in with 70 sx Class "B" 50:50 Poz, 6% gel. Circulated 2 bbls. cement.

Rig released 11/12/77.

18. I hereby certify that the foregoing is true and correct

SIGNED

E. E. Sushoda

TITLE Area Adm. Supervisor

DATE 11/30/77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE RECEIVED

CONDITIONS OF APPROVAL, IF ANY:

DEC 2 1977

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
Farmington, N.M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.