

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0560422

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

EL PASO

9. WELL NO.

1A

10. FIELD AND POOL, OR WILDCAT

BLANCO MESA VERDE

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 20, T-29-N, R-9-W

NMPM

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR

BOX 990, FARMINGTON, NEW MEXICO 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

500'N, 1840'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5559' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*1/8/78: T.D. 2331'. Ran 58 joints 7", 20#, K-55 intermediate casing, 2316' set  
at 2331'. Cemented with 322 cu. ft. cement. WOC 12 hours, held 1200#/  
30 minutes. Top of cement at 525'.1/12/78: T.D. 4723'. Ran 79 joints 4 1/2", 10.5#, KS casing liner, 2560' set  
2163-4723'. Float collar set at 4706'. Cemented with 443 cu. ft.  
cement. WOC 18 hours.2/20/78: PBTD 4706'. Tested casing to 3500#, OK. Perfed C.H. and Men. 3652,3660,  
3713,3719,3835,3845,4029,4035,4096,4152,4168,4174,4180,4187' w/1 SPZ.  
Fraced with 40,000# 20/40 sand and 72,100 gal. water. Flushed with  
5000 gallons water. Perfed P.L. 4284,4290,4296,4302,4318,4324,4330,4342,  
4349,4355,4361,4409,4439,4444,4461,4490,4501,4521,4548,4566,4582,4675'  
w/1 SPZ. Fraced with 63,000# 20/40 sand and 104,800 gallons water.  
Flushed w/5100 gal. water.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. BlascoTITLE Drilling ClerkDATE 2/21/78

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

RECEIVED

FEB 23 1978

\*See Instructions on Reverse Side