Location of Well: K-18-29-9 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #: RTU: -County: SAN JUAN Meter #: TYPE PROD METHOD PROD MEDIUM PROD NAME RESERVOIR OR POOL GAS FLOW TBG UPR VALENCIA GC B # IM - MV COMP GAS FLOW TBG LWR VALENCIA GC B #IM - PK COMP PRE-FLOW SHUT-IN PRESSURE DATA Hour/Date Shut-In | Length of Time Shut-In SI Press. PSIG Stabilzed 1a / a /95 UPR COMP Yes 72 Hes 329 LWR 1a/a/95 COMP 72 HES Yes 220 FLOW TEST DATE NO.1 Zone Producing (Upr(Lwr)) Commenced at (hour, date) * LAPSED TIME PRESSURE Prod TIME Temp. REMARKS Upper SINCE* Lower (hour, date) Both Zones SI Day 1 12 /a /95 212 203 Both Zones SI 12 /3 /95 Day 2 253 210 Both Zones SI 12 /4 /95 Day 3 215 272 la /5 /95 Day 4 329 220 from Lower Zone 95/ ط/ جا Day 5 213 331 Day 6 12 /7 /95 207 337 Production rate during test Hrs Grav GOR ___ Oil: BOPD based on BBLs in MFCPD: Tested theu (Orifice or Meter): METER Gas: MID-TEST SHUT-IN PRESSURE DATA Stabilized (yes/no) Length of Time SI SI Press. PSIG Hour, Date SI UPR COMP LWR COMP

(Continue on reverse side)

FLOW TEST NO. 2

Commonced at Mour, data) # #				Zene producing (Upper or Lewer):	
THEE Shour, delet	LAPSED TIME	Voser Completion	NE Lewer Completion	PROD. ZONE TEMP,	REMARKS
(100, 00 to)	ance + +	Opput Completion		icay.	
					
<u> </u>					
					·
	<u> </u>	<u> </u>	<u> </u>	<u> </u>	1
Production rate during test					
Oil: BOPD based on Bbls. in Hours Grav GOR					
Gas: MCFPD: Tested thru (Orifice or Meter):					
Remarks:					
I hereby certify that the information herein contained is true and complete to the best of my knowledge.					
Approved	Johnny Rol	unsen	19 (Operator	Amoco Production Company
Approved Jehrny Rollinson 19 New Mexico Oil Onservation Division				4.	Then Bradshaw 8
	DEC 1 3			-	
Ву	DEDITY ON R CAS	BUTTER	7	Tide	Field Tech
Tide	DEPOTE OIL & GAS	S GRON LOTON		Date1&	11/95

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fractive treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distributed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure trabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Ten No. 1, one lone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such ten shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage tent, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced 2000 shall remain shut-in while the 2000 which was previously shut-in is produced.
- 7. Pressures for gas-200e tests must be measured on each 200e with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone testi: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aster District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas roots only) and gravity and GOR (oil zones only).