

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well:

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FSL, 1480' FFL, Sec. 34, T29N, R8W, N.M.P.M.

5. Lease Designation and Serial No.

SF-078049A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Bolin A 3

9. API Well No.

30-045-26446

10. Field and Pool, or exploratory Area

Blanco Picture Cliff

11. County or Parish, State

San Juan NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was plugged and abandoned on 5/20/99 as per the attached plugging summary.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Foreman

Date 6/14/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

NMOC

JUN 15 1999

FIELD OFFICE

# **A - PLUS WELL SERVICE, INC.**

P.O. BOX 1979  
FARMINGTON, NM 87499  
505-325-2627 • FAX: 505-325-1211

---

Energen Resources Corporation

May 21, 1999

## **Bolin A #3**

1850' FSL and 1480' FEL Sec. 34, T-29-N, R-8-W  
San Juan County, NM  
SF-078049A

## **Plug & Abandonment Report**

### **Cementing Summary:**

**Plug #1** with 69 sxs Class B cement pumped down 2-7/8" casing with 2% CaCl<sub>2</sub> to fill Pictured Cliffs perforations and to cover Fruitland, Kirtland and Ojo Alamo tops, displaced to 1000'.

**Plug #2** with 154 sxs Class B cement pumped down 2-7/8" casing from 580' to surface, circulate good cement out bradenhead.

### **Plugging Summary:**

Notified BLM on 5/18/99

5-18-99 Safety Meeting. Road rig and equipment to location, spot in. SDFD.

5-19-99 Safety Meeting. Open well, no pressure. Pump 20 bbls water 3-1/2 bpm at 0# with no blow on bradenhead. Drop 15 7/8" RCN balls and pump 15 bbls water at 3-1/2 bpm at 0#, pressured up to 250#. Pump additional 4 bbls water 3.5 bpm at 250# with no blow on bradenhead. Plug #1 with 69 sxs Class B cement pumped down 2-7/8" casing with 2% CaCl<sub>2</sub> to fill PC perforations and to cover Fruitland, Kirtland and Ojo Alamo tops, displaced to 1000'. Shut in well and WOC 3 hours. RU A-Plus wireline truck and tag cement at 1331'. Perforate 3 bi-wire squeeze holes at 580'. Establish rate into holes 2 bpm at 300#. Pump 9 bbls water to establish circulation out bradenhead. Plug #2 with 154 sxs Class B cement pumped down casing from 580' to surface, circulate cement out bradenhead. SI well, SDFD.

5-20-99 Open up well, cement at surface in 2-7/8" casing. Dig out and cut off wellhead, cement down 25' in 8-5/8" annulus. Mix 20 sxs Class B cement, fill annulus and install P&A marker. RD cement equipment; move off location.  
No BLM representative was location.