

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

SF078201

6. If Indian, Allottee or Tribe Name

-

7. If Unit or CA, Agreement Designation

-

8. Well Name and No.

Federal 29-9-12 #2

9. API Well No.

30-045-28738

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

SG Interests I, Ltd.

3. Address and Telephone No.

P. O. Box 421, Blanco, NM 87412-0421 (505) 325-5599

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1002' FNL & 867' FEL
Section 12, T29N, R9W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

Production Casing

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Production Casing: TD @ 3081' on 9-23-92.

Hole Size: 7 7/8"

Casing: 72 Jts (3065') 5 1/2", 15.5#, J-55, Casing set @ 3076', Guide Shoe @ 3076', Float Collar @ 3030', Centralizers @ 3076', 3014', 2930', 2846', 2762', 2678', 2594', 2510', 2426', 2342', 2258', & 2174'.

Cement: 450 sx Pacesetter Lite w/690 gel (1.92 Yield/868 cu ft) & 100 sx Class B w/2.9 CF-14 w/0.490 Thrifty Lite (1.19 Yield/119 cu ft). Top of cement will be determined upon completion when CBL is run (No cement circ to surface).

Bump Plug w/1000 psi - Held OK:

Plug Down @ 1:30 PM on 9/24/92.

RECEIVED
BLM
OCT 01 11:00 AM '92
FARMINGTON, NM

RECEIVED
OCT 03 1992
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Camie A. Baze

Title Agent (915) 694-6107

Date 9/28/92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

OCT 07 1992