

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

**OIL CONSERVATION DIVISION**

**DISTRICT I**  
P.O. Box 1980, Hobbs NM 88241-1980

**DISTRICT II**  
P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-045-30436

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Lackey

8. Well No.  
4R

9. Pool name or Wildcat  
Aztec Pictured Cliffs

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO CHANGE A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator ENERGEN RESOURCES CORPORATION	
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401	
4. Well Location Unit Letter <u>G</u> : <u>2430</u> Feet From The <u>North</u> Line and <u>1765</u> Feet From The <u>East</u> Line Section <u>19</u> Township <u>29N</u> Range <u>9W</u> NMPM San Juan County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5617' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: Spud ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

02/14/01 SPUD 11:00 am 02/14/01. Drill 12 1/4" hole to 285'. Ran 6 jts. 9 5/8" 36# J-55 ST&C casing, set at 285'. RU Halliburton. Cement with 150 sks. Class B, 1/4#/sk flocele and 2% CaCl2 (177 cu. ft.). Plug down @ 9:30 am 02/14/01. Circulate 35 sks cement to surface. RD Halliburton. WOC. Test BOP and casing to 600 psi - OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 02/15/01

TYPE OR PRINT NAME Vicki Donaghey TELEPHONE NO. 505-325-6800

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERDUE

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

DEPUTY OIL & GAS INSPECTOR, DIST. 3 FEB 16 2001