

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 079485

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1790'N, 1650'W

7. UNIT AGREEMENT NAME

San Juan 30-4 Unit

8. FARM OR LEASE NAME

San Juan 30-4 Unit

9. WELL NO.

34

10. FIELD AND POOL, OR WILDCAT

East Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 16, T-30-N, R-4-W
NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7452'GL

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-19-73 TD 4580'. Ran 144 joints 2 7/8", 6.4#, J-55 production casing, 4570' set at 4580'. Baffle set at 4570'. Cemented with 309 cu.ft. cement. WOC 18 hours. Top of cement at 2700'.

10-25-73 Tested casing to 4000#-OK. PBTD 4570'. Perf'd 4240', 4266', 4274', 4426', 4434', 4476' and 4484' with 7 holes. Frac'd with 70,000# 10/20 sand and 81,900 gallons treated water. Dropped one set of 10 balls. Flushed with 1100 gallons water.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Clerk

DATE

October 31, 1973

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE