APPROVED BY _______CONDITIONS OF APPROVAL, IF ANY:

5. LEASE

SF 079382

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 30-6 Unit
reservoir, use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas x ell other	San Juan 30-6 Unit
2. NAME OF OPERATOR	9. WELL NO. 72A
El Paso Natural Gás Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco MV
Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA Sec. 22, T-30-N, R-7-W N.M.P.M.
AT JOB BROD INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15 CLEVATIONS (SUCCESS
·	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6638' G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0030 0.1.
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all portions details and sing and single
THE DESCRIPE FROM USED OR COMPLETED OPERATIONS (CLASSIV STATE	can pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinen	t to this work.)*
79: PBTD 6161'. Tested casing to 3500#, OK, Per 5794,5815,5821,5834,5839,5844,5849,5854,586 6052,6058,6089,6118,6151'. W/1 SPZ. Frace gal. water. Flushed w/7,686 gal. water. 5405,5412,5454,5481,5526,5532,5550,5557,556	fed P.L. 5745, 5752,5767,5776,578 3,5885,5904,5936,5958,6002,6037, d w/83,000# 20/40 sand, 166,000 Perfed 5332, 5377, 5384,5391,539 4,5577,5584,5591,5629,5663! W/1
79: PBTD 6161'. Tested casing to 3500#, OK, Per 5794,5815,5821,5834,5839,5844,5849,5854,586 6052,6058,6089,6118,6151'. W/1 SPZ. Frace gal. water. Flushed w/7,686 gal. water.	fed P.L. 5745, 5752,5767,5776,578 3,5885,5904,5936,5958,6002,6037, d w/83,000# 20/40 sand, 166,000 Perfed 5332, 5377, 5384,5391,539 4,5577,5584,5591,5629,5663! W/1
79: PBTD 6161'. Tested casing to 3500#, OK, Per 5794,5815,5821,5834,5839,5844,5849,5854,586 6052,6058,6089,6118,6151'. W/1 SPZ. Frace gal. water. Flushed w/7,686 gal. water. 5405,5412,5454,5481,5526,5532,5550,5557,556 Fraced w/67,000# 20/40 sand, 134,000 gal. w	fed P.L. 5745, 5752,57675776,578 3,5885,5904,5936,5958,6002,6037, d w/83,000# 20/40 sand, 166,000 Perfed 5332, 5377, 5384,5391,539 4,5577,5584,5591,5629,5663' W/1 ater. Flushed w/7,434 gal. water
79: PBTD 6161'. Tested casing to 3500#, OK, Per 5794,5815,5821,5834,5839,5844,5849,5854,586 6052,6058,6089,6118,6151'. W/1 SPZ. Frace gal. water. Flushed w/7,686 gal. water. 5405,5412,5454,5481,5526,5532,5550,5557,556 Fraced w/67,000# 20/40 sand, 134,000 gal. w	fed P.L. 5745, 5752,5767,5776,578 3,5885,5904,5936,5958,6002,6037, d w/83,000# 20/40 sand, 166,000 Perfed 5332, 5377, 5384,5391,539 4,5577,5584,5591,5629,5663! W/1
79: PBTD 6161'. Tested casing to 3500#, OK, Per 5794,5815,5821,5834,5839,5844,5849,5854,586 6052,6058,6089,6118,6151'. W/1 SPZ. Frace gal. water. Flushed w/7,686 gal. water. 5405,5412,5454,5481,5526,5532,5550,5557,556 Fraced w/67,000# 20/40 sand, 134,000 gal. w	fed P.L. 5745, 5752,5767,5776,578 3,5885,5904,5936,5958,6002,6037, d w/83,000# 20/40 sand, 166,000 Perfed 5332, 5377, 5384,5391,539 4,5577,5584,5591,5629,5663' W/1 ater. Flushed w/7,434 gal. water

AUG 1 6 1979

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY DURANGO, COLO.