

& NATURAL RESOURCES DEPARTMENT

GE, CONSERVATION GRASION
ACTED GISTRICT OFFICE
1600 RIO BRAZOS ROAD
ACTED INIC 67410
(500) 384-6179 FAX: (500) 334-6170
IMPLIANCE INIC STANCE INICIALIZATION IN THE INICIALIZATION INICIALIZATION IN THE INICIALIZATION INICIALIZ

This form is not to be used for reporting packer leaings tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

erator Ph	illips Petrole	um Co. 017654	Lease Name	San Juan	30-5 Unit	Well No ⁷⁴
cation of \	Well:Unit Letter_	KSec34	Twp_30N	_Rge_ ^{5W}	API # 30-0 _39-227	54
	NAME OF RESER	VOIR OR POOL	TYPE OF		METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUN (Tbg. or Csg.)
Upper Completion	Pictured Clif	fs	gas		flowing	tubing
Lower Completion	Mesaverde		gas		flowing	tubing
		PRFJ	LOW SHUT-I	N PRESSURE	DATA	
Upper Completion	Hour, date shut-in		Length of time		Si press. Psig	Stabilized? (Yes or No
Lower Completion	Hour, date shut-in	Hour, date shul-in		shut-in	SI press. Psig	Stabilized? (Yes or No
Completion			FLOW TE	ST NO. 1		
Commenced &	(hour, dele)*			Zone producing ((Upper or Lower):	
TIME (hour,date)	LAPSED TIME PRESSU		SURE	PROD. ZONE	REMARKS	
	SINCE*	Upper Completion	Lower Completion	CM.		
					10 19 20 21 22	
					NOV 2001	
	-				ON CON DIV	
					DIST. 3	60 9
Production	rate during test				Cesta De	
Oil:			d on			GravGOR
Gas:	· · · · · · · · · · · · · · · · · · ·	-			Meter):	
		MI	O-TEST SHUT	_		
Upper Completio	Hour, date shut-in		Length of tin	ne shut-in	SI prece pelg	Stabilized? (Yes or
Lower	Hour, date shut-in		Length of tir	ne shut-in	SI press, psig	Stabilized? (Yes or

(Continue on reverse side)

100 //m

30-5# 74 "FLOW TEST NO. 2									
Commenced at (hour, de		-01	Zone producing (Upper er Lower):						
TIME	LAPSED TIME	PC PRESSURE MV		PROD. ZONE					
(hour, dete)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS				
11-15-01		1018#	310#						
		90#	9510H		Blow PC down to 90#				
Production rate d	luring test								
Oil:	BOI	D based on	Bbls. in	Hour	s Grav GOR				
Gas:	···	мсі	PD: Tested thru	(Orifice or Mete	:r):				
Remarks:									
I hereby carrify t	hat the informat	ion herein contair	ed is true and co	mplete to the be	est of my knowledge.				
· · · · · · · · · · · · · · · · · · ·					۸ .				
Approved	11/15/	200 1	19C	perator <u>D</u>	helles Petroloun				
New Mexico O	il Conservation	Division	P	v Jim	Kennedy				
By Sku	ice M	1 anti-		itle Fee	Kennedy.				
· 1		1+625 I		Date//-					

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was prev ly shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwe pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beging of each flow-period, at fifteen-minute intervals during the first hour thereof, as hourly intervals thereafter, including one pressure measurement immediately prior to conclusion of each flow period. 7-day tests: immediately prior to the beginning of flow period, at least one time during each flow period (at approximately the mir point) and immediately prior to the conclusion of each flow period. Other pressures be taken as desired, or may be requested on wells which have previously shown a tionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continued and recorded with recording pressure gauges the accuracy of which musthecked at least twice, once at the beginning and once at the end of each test, we deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recing gauge shall be required on the oil zone only, with deadweight pressures as required on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days completion of the test. Tests shall be filed with the Aztec District Office of the New M. Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Re 10-01-78 with all deadweight pressures indicated thereon as well as the flo temperatures (gas zones only) and gravity and GOR (oil zones only).