

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>	7. UNIT AGREEMENT NAME San Juan 30-6 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 30-6 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WELL NO. 455
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1080'S, 1510'W	10. FIELD AND POOL, OR WILDCAT Undes. Fruitland Coal
14. PERMIT NO.	15. ELEVATIONS (Show whether DP, RT, GR, etc.) 6629' GL
	11. SEC., T., R. M., OR S.E. AND SURVEY OR AREA Sec. 18, T-30-N, R-06-W N.M.P.M.
	12. COUNTY OR PARISH 13. STATE Rio Arriba NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

Running Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

07-09-88 TD 3330'. Ran 78 jts. 7", 20.0#, K-55 intermediate casing, 3317' set @ 3330'. Cemented with 500 sks. Class "G" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (920 cu.ft.) followed by 100 sks. Class "G" with 2% calcium chloride (112 cu.ft.). WOC 12 hours. Held 1200#/30 min. Circ. to surface

08-08-88 TD 3537'. Ran 7 jts. 5 1/2", 23.0#, P-110 casing liner, 298' set @ 3537'. Float shoe set @ 3537'. Top of liner hanger @ 3239'. Did not cement.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Regulatory Affairs

DATE

09-08-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side