

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1865' FSL & 1595' FWL
Section 5, T-30-N, R-6-W

5. Lease Designation and Serial No.

NM-03404

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 31-6 Unit

8. Well Name and No.

#213

9. API Well No.

30-039-24531

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Cavitate & cmt liner
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-21-94

MIRU Big A #19 to cavitate & cement the liner on the abovementioned well. ND WH & NU 10" BOPs & X-overs. Tested BOPs. RIH & covered coal interval with sand. Set cement retainer at 2930' and cemented liner with 115 sxs C1 B & 2#/sx Hi-seal + 5% CF-1, (24 bbls cement @ 15.6 slurry wt., slurry yld 1.18). Set packer and squeezed liner top w/60 sxs C1 B Neat cement. POOH w/packer. Drilled out liner top and cement retainer. Cleaned out to TD. Cavitated well with air, foamer and water. RIH w/2-3/8" 4.7# J-55 8rd EUE tubing and set at 3083'. RD and released rig 1800 hrs on 11-7-94.

RECEIVED
NOV 22 1994
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Ed Harsely

Title Environmental/Regulatory Eng.

Date 11-9-94

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

400PTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

FARMINGTON, NM 87401