

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*

(See other instructions on reverse side)

FOR APPROVED  
OMB NO. 1004-0137  
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG \*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other \_\_\_\_\_  
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REMVR. ☐ Other \_\_\_\_\_

2. NAME OF OPERATOR  
Burlington Resources Oil & Gas Company  
3. ADDRESS AND TELEPHONE NO.  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*  
At surface 820' FSL, 1825' FEL  
At top prod. interval reported below  
At total depth

14. PERMIT NO. DATE ISSUED

5. LEASE DESIGNATION AND SERIAL NO.  
NM-012709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 30-6 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 30-6 U #10A

9. API WELL NO.

30-039-25601

10. FIELD AND POOL OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 31, T-30-N, R-7-W

12. COUNTY OR PARISH

Bio Arriba NM

15. DATE SPUDDED 11-17-96 16. DATE T.D. REACHED 11-22-96 17. DATE COMPL. (Ready to prod.) 12-17-96 18. ELEVATIONS (DP, RKB, RT, GR, ETC.)\* 6034 GR, 6046 KB 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 5473 21. PLUG BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY\* 23. INTERVALS DRILLED BY 0-5473 24. ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME, MD, AND ELEV. 4405-5344 Mesaverde 25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN GR-CNL 27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)  
CASING SIZE/GRADE WEIGHT, LB./FT. DEPTH SET (MD) HOLE SIZE TOP OF CEMENT, CEMENTING RECORD AMOUNT PULLED  
9 5/8 36# 244 12 1/4 224 cu.ft.  
7 23# 3067 8 3/4 699 cu.ft.

29. LINER RECORD 30. TUBING RECORD  
SIZE TOP (MD) BOTTOM (MD) SACKS CEMENT\* SCREEN (MD) SIZE DEPTH SET (MD) PACKER SET (MD)  
4 1/2 2907 5471 482 cu.ft. 2 3/8 5350

31. PERFORATION RECORD (Interval, size and number)  
4405, 4491, 4528, 4543, 4607, 4620, 4627, 4634, 4642, 4648, 4658, 4669, 4684, 4691, 4695, 4701, 4707, 4748, 4757, 4780, 4791, 4797, 4840, 4849, 4909, 4913, 4921, 4932, 4958, 4972,  
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.  
DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED  
4405-4849 2901 bbl 28 KCL slk wtr  
120,000# 20/40 Ariz sd  
4909-5344 3017 bbl slk wtr  
120,000# 20/40 Brady sd

33. Continued on back PRODUCTION  
DATE FIRST PRODUCTION 12-17-96 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing WELL STATUS (Producing or abandoned) 90 SI  
DATE OF TEST 12-17-96 HOURS TESTED CHOKER SIZE PROD'N. FOR TEST PERIOD OIL—BSL. GAS—MCF. WATER—BSL. GAS-OIL RATIO  
12-17-96 1626 Pitot Gauge 1 EEC  
FLOW. TUBING PRESS. CASING PRESSURE CALCULATED 24-HOUR RATE OIL—BSL. GAS—MCF. WATER—BSL. OIL GRAVITY API (CORR.)  
SI 418 SI 556

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold TEST WITNESSED BY

35. LIST OF ATTACHMENTS None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records  
SIGNED [Signature] TITLE Regulatory Administrator DATE 12-27-96  
FARMINGTON DISTRICT OFFICE

\*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

| FORMATION             | TOP   | BOTTOM | DESCRIPTION, CONTENTS, ETC.                                                    |
|-----------------------|-------|--------|--------------------------------------------------------------------------------|
| Ojo Alamo             | 1760' | 1950'  | White, cr-gr ss.                                                               |
| Kirtland              | 1950' | 2382'  | Gry sh interbedded w/tight, gry, fine-gr ss.                                   |
| Fruitland             | 2382' | 2850'  | Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.         |
| Pictured Cliffs       | 2850' | 3030'  | Bn-Gry, fine grn, tight ss.                                                    |
| Huerfanito Bentonite* | 3605' | 3870'  | White, waxy chalky bentonite                                                   |
| Chacra                | 3870' | 4393'  | Gry fn grn silty, glauconitic sd stone w/drk gry shale                         |
| Cliff House           | 4393' | 4708'  | ss. Gry, fine-grn, dense sll ss.                                               |
| Menefee               | 4708' | 5050'  | Med-dark gry, fine gr ss, carb sh & coal                                       |
| Point Lookout         | 5050' | 5420'  | Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation |
| Mancos                | 5420' | 5473'  | Dark gry carb sh.                                                              |

38. GEOLOGIC MARKERS

|                  | TOP         |                  |
|------------------|-------------|------------------|
|                  | MEAS. DEPTH | TRUE VERT. DEPTH |
| Ojo Alamo        | 1760'       |                  |
| Kirtland         | 1950'       |                  |
| Fruitland        | 2382'       |                  |
| Pic. Cliffs      | 2850'       |                  |
| Lewis            | 3030'       |                  |
| Huerfanito Bent. | 3605'       |                  |
| Chacra           | 3870'       |                  |
| Cliff House      | 4393'       |                  |
| Menefee          | 4708'       |                  |
| Pt. Lookout      | 5050'       |                  |
| Mancos           | 5420'       |                  |

\*Huerfanito Bentonite is the legal top of Mesa Verde in New Mexico (North of the Chacra line)

Perforations continued: 4975, 5022, 5058, 5068, 5076, 5088, 5097, 5108, 5116, 5127, 5152, 5156, 5176, 5185, 5192, 5206, 5265, 5278, 5297, 5316, 5326, 5344

