

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit M, 550' FSL & 485' FWL  
Section 11, T30N, R5W

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-080538

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 Unit 257

9. API Well No.

30-039-25718

10. Field and Pool, or exploratory Area

Basin Fruitland Coal

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud report
- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/3/97

MIRU Big A #41. Spud 12-1/4" hole @ 1930 hrs 9/3/97. Drilled to 372'. RU & RIH w/9-5/8" 36# K-55 ST&C casing and set @ 369'. RU BJ to cement - Pumped 185 sx (222 cu ft) Class B cement, 2% CaCl<sub>2</sub>, 1/4#/sx cello-flake, mixed @ 15.6 ppg w/1.20 yield. Rate 1-3 bpm @ 200 psi. Bumped plug. Left 30 ft cement in casing and had 12 bbls (67 sx - 80.4 cf) cement returns to surface. WOC 8 hrs. NU BOPs. Test casing @ 200 psi - 3 min and 1500 psi - 30 min. Good test.

RECEIVED  
SEP 12 1997

OIL COAL DIV.  
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Regulatory Assistant Date 9-10-97

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval, if any: \_\_\_\_\_

ACCEPTED FOR RECORD

SEP 10 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instruction on Reverse Side

NMOCD

FARMINGTON DISTRICT OFFICE  
BY [Signature]