STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

3624602

351

OIL CONSERVATION DIVISION

API# 30-039-25837

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

						Well	
erator B	URLINGTON RESOURCE	ES OIL & GAS CO.	Lease	SAN JUAN 30	0-6 UNII	No. 43A	
ation Well:	Unit I Sect	14 Twp. 0301		006W	County RIO ARRIBA		
	NAME OF	RESERVOIR OR POOL	T	YPE OF PROD.	METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)	
				(Oil or Gas)	(Flow of Art. Lift)		
Upper ompletion	MESAVERDE		· .	Gas	Flow	Tubing	
Lower ompletion	DAKOTA			Gas	Flow	Tubing	
			SHUT-IN PRESS				
Upper	Hour, date shut-in	Length of time shut-in		ress. psig	Stabilized? (Yes or No)		
ompletion	04/17/2002	168 Hours		260			
Lower Completion	04/17/2002	120 Hours	: 	742			
		F	LOW TEST NO.				
Commenced	enced at (hour.date)* 04/22/2002			Zone producing (Upper or Lower)		OWER	
TIME	LAPSED TIME	PRESSURE		PROD. ZONE		AAADI'C	
hour.date)	SINCE*	Upper Completion Lov	ver Completion	TEMP	KE KE	MARKS	
4/23/2002	144 Hours	260	182				
)4/24/2002	168 Hours	260	210		·		
					Line pressure up 28	B#.	
					:		
				-			
					:		
oduction rat	te during test			_!			
il	BOPD based on	Bbls. in	Hour	S	Grav.	GOR	
as:		MCFPD; Tested thru (Orific	ce or Meter):				
		MID-TEST	SHUT-IN PRES	SURE DATA			
Upper Completion	Hour, date shut-in	Length of time shut-in		press. psig	Stabilized?	(Yes or No)	
Lower Completion	Hour. date shut-in	Length of time shut-in	SI	press. psig	Stabilized?	(Yes or No)	

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, d	ate)**		Zone producing (Upper or Lower):				
TIME (hour, date)	LAPSED TIME SINCE **	PRES Upper Completion	r	PROD.		REMARKS	
		Upper Completion	Lower Completi	on			
				<u> </u>			
Production rate du	ring test						
Oil:	ВС	OPD based on	Bbls. ir	н Н	ours	Grav GOR	
Gas:		МСГРІ	D: Tested thru (0	Orifice or Meter	·):		
Remarks:	· • · · · ·						
I hereby certify tha	it the information he $1AY - 27$	rein contained is true	and complete to	o the best of my	knowledg	e.	
		19				on Resources	
New Mexico Oil Conservation Division				By L	By Odoro air		
Bv	ML SHOWED BY CH			Title Ope	•	0	
		PTCIVE, EST. S.					
Title		Date Wednesday, May 01, 2002					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: immediately prior to the beginning of each flow period, at fitteen-minute intervals during the first hour thereof: and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azrec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).