Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED			
Budget Bure			
Expires:	March 31,	1993	

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. SF-078997 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well San Juan 30-5 Unit Oil 8. Well Name and No. 2. Name of Operator SJ 30-5 Unit #220 Phillips Petroleum Company 9. API Well No. 3. Address and Telephone No. 30-039-26045 5525 Highway 64, NBU 3004, Farmington, NM 10. Field and Pool, or exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit K, 1515' FSL & 1495' FWL Basin Fruitland Coal Section 8. T30N. R5W 11. County or Parish, State Rio Arriba, CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Spud Report Other Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 2/24/99

MIRU Big A #37. Spud 12-1/4" hole @ 0430 hrs 2/25/99. Drilled ahead to 372'. RIH w/9-5/8" 36#, K-55 casing and landed @ 356'. RU BJ to cement. Pumped 10 bbls mud flush and 10 bbl water spacer ahead of 185 sx (225 cf) of Class H cement w/2% CaCl2 & 1/4#/sx Cello-flake, mixed at 15.6 ppg w/1.20 yield. Dropped wood plug & displaced with 27 bbls of water. Plug down @ 1750 hrs 2/25/99. Circulated 10 bbls (56 cf) cement returns to surface. WOC. NU WH & NU BOP. PT blinds rams, casing and lines to 200 psi 3 minutes and 1500 psi for 10 minutes. Good test.

,		
14. I hereby certify that the foregoing is true and correct Signed Title	Regulatory Assistant	Date 2-26-99
(This space for Federal or state office use) Approved by Title Conditions of approval, if any:		Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

MAR 0 5 1999