

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

ENERGEN RESOURCES CORPORATION

3. Address and Telephone No.

2198 Bloomfield Highway, Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2315' FSL, 1000' FWL, Sec. 27, T30N, R4W, N.M.P.M.

5. Lease Designation and Serial No.

NMSF-079482

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Carson

7

9. API Well No.

30-039-26196

10. Field and Pool, or exploratory Area

East Blanco Pictured Cliffs

11. County or Parish, State

Rio Arriba

NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☒ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 4560'. RU Halliburton. Log well w/HRI/SP/GR, CNT/LDT/MLT, MRIL. Ran 101 jts. 4-1/2" 10.5# J-55 ST&C casing, set @ 4556', stage tool @ 3702'. RU Halliburton & cement 1st stage w/260 sks. Class "H", 2% CaCl2, 10#/sk gilsonite, 1/4#/sk flocele(325 cu. ft.) Plug down @ 1:15 AM 9/10/00. Open stage tool & circ. 20 sks. cement to surface. Cement 2nd stage w/700 sks. Class "H", 6% gel, 2% CaCl2, 10#/sk gilsonite, 1/4#/sk flocele(1372 cu. ft.) followed w/100 sks Class "H", 2% CaCl2, 10#/sk gilsonite, 1/4#/sk flocele(125 cu. ft.) Plug down @ 12:15 PM 9/10/00. Circ. 200 sks. cement to surface. Rig released @ 4:15 PM 9/10/00.

14. I hereby certify that the foregoing is true and correct

Signed

*Don Graham*

Title Drilling & Completion Foreman

9/11/00  
ACCEPTED FOR RECORD

(This space for Federal or State office use)

Approved by

Title

Date

OCT 26 2000

Conditions of approval, if any:

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.