

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐				5. LEASE DESIGNATION AND SERIAL NO. SF-08071ZA	
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR EURLINGTON RESOURCES OIL & GAS COMPANY				7. UNIT AGREEMENT NAME San Juan 30-6 Unit	
3. ADDRESS AND TELEPHONE NO. PO Box 4289, Farmington, NM 87499 (505) 326-9700				8. FARM OR LEASE NAME, WELL NO. San Juan 30-6 Unit #130	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1800'FNL, 1520'FEL, At top prod. interval reported below At total depth				9. API WELL NO. 30-039-26216	
14. PERMIT NO. DATE ISSUED				12. COUNTY OR PARISH Rio Arriba	
15. DATE SPUNDED 11-12-99				13. STATE New Mexico	
16. DATE T.D. REACHED 11-16-99		17. DATE COMPL. (Ready to prod.) 5-4-00		10. FIELD AND POOL, OR WLDGAT WC:30N6W28G Pict.Cliffs	
20. TOTAL DEPTH, MD & TVD 3725'		21. PLUG, BACK T.D., MD & TVD		11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 28, T-30-N, R-6-W	
22. IF MULTIPLE COMPL., HOW MANY*		23. INTERVALS DRILLED BY		19. ELEV. CASINGHEAD	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* 3269-3610' Pictured Cliffs				25. WAS DIRECTIONAL SURVEY MADE	
26. TYPE ELECTRIC AND OTHER LOGS RUN AIT-GR				27. WAS WELL CORED Yes - sidewall cores	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	143'	12 1/4"	189 cu.ft.	
4 1/2"	10.5#	3703'	6 1/4"	2047 cu.ft.	
29. LINER RECORD					
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	PACKER SET (MD)
				2 3/8"	3305'
31. PERFORATION RECORD (Interval, size and number)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
3169, 3172, 3175, 3190, 3193, 3196, 3199, 3202, 3205, 3269, 3271, 3274, 3277, 3280, 3283, 3285, 3287, 3289, 3291, 3293, 3295, 3297, 3299, 3301, 3304, 3307, 3310, 3360, 3364, 3368, 3372, 3376, 3380, 3440, 3444, 3448, 3452, 3456, 3460, 3510, 3514, 3518, 3522, 3526, 3530, 3590, 3594, 3598, 3602, 3606, 3610'			DEPTH INTERVAL (MD)		
			317 bbl 20# linear gel, 85,000# 20/40 Arizona sd		
			504,900 SCF N2		
			Squeeze @ 3169-3205'		
			75 sx Class "B" neat cmt w/0.4% fluid loss, 2% calcium chloride		
33. PRODUCTION					
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump)		WELL STATUS (Producing or shut-in)	
		Flowing		SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF
5-4-00	1				TSTM - Pitot Gauge
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL
SI 337	SI 357				
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)				TEST WITNESSED BY	
To be sold				ACCEPTED FOR RECORD	
35. LIST OF ATTACHMENTS None					

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [Signature] TITLE Regulatory SupervisorDATE 5-12-00

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

JUN 09 2000

BY [Signature] FIELD OFFICE

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof, cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Ojo Alamo	2384'	2490'	White, cr-gr ss.
Kirtland	2490'	2658'	Gry sh interbedded w/tight, gry, fine-gr ss.
Fruitland	2658'	3156'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
Pictured Cliffs	3156'	3398'	Bn-Gry, fine grn, tight ss.

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	2384'	
Kirtland	2490'	
Fruitland	2658'	
Pic.Cliffs	3156'	

Sidewall Cores @ 3167, 3175, 3189, 3203, 3212, 3219, 3225, 3261, 3265, 3269, 3273, 3281, 3295, 3302, 3307, 3311, 3346, 3358, 3366, 3373, 3391, 3431, 3473, 3539' for 24 cores total