

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-039-26640
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-347-39

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	7. Lease Name or Unit Agreement Name: San Juan 30-5 Unit 009258
2. Name of Operator Phillips Petroleum Company	8. Well No. SJ 30-5 Unit #219R
3. Address of Operator 5525 Highway 64, NBU 3004, Farmington, NM 87401	9. Pool name or Wildcat Basin Fruitland Coal 71629
4. Well Location Unit Letter <u>L</u> : <u>2627'</u> feet from the <u>South</u> line and <u>662'</u> feet from the <u>West</u> line Section <u>16</u> Township <u>30N</u> Range <u>5W</u> NMPM County <u>Rio Arriba</u>	
10. Elevation (Show whether DR, RK3, RT, GR, etc.) 6335' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐

OTHER: ☐ OTHER: 7" casing report ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

RIH w/8-3/4" bit & tagged up @ 205'. Drilled cement and then formation to 3017'. Circ. hole. RIH w/7". 20#, J-55 casing and set @ 3013. RU to cement. Pumped 10 bbls mud clean, 10 bbls FW w/red dye in last 5 bbls. Then pumped Lead - 420 sx (997.9 cf - 177.73 bbl slurry) Type 3 cement 35/65 POZ w/5#/sx Gilsonite, 1/4#/sx Cello-flake, 6% Gel, 10#/sx CSE, 3% KCl, 0.4% FL-25, 0.02#/sx Static Free.

Pumped Tail - 50 sx (70 cf - 12.46 bbl slurry) Type 3 cement w/1/4#/sx Cello-flake, 1% CaCl2. Dropped wood plug & displaced w/120 bbls FW. Bumped plug w/1200 #. Held good. Circulated 10 bbls cement to surface. WOC. ND BOP. NU WH. PT casing, rams, and maniofld to 200 psi 3 minutes and 2000 psi for 10 minutes. Good test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Patsy Clugston TITLE Sr. Regulatory/Proration Clerk DATE 2/5/01

Type or print name Patsy Clugston Telephone No. 505-599-3454

(This space for State use)
ORIGINAL SIGNED BY CHANCE T. PETERSON

OFFICIAL OIL & GAS INSPECTOR, STATE OF NM

FEB - 8 2001

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any:

4