


FROM	TO	THICKNESS IN FEET	FORMATION
Surface	50'	50'	Surface & valley fill
50'	140'	90'	Sand & shale
140'	210'	70'	Ojo Alamo conglomerate
210'	290'	80'	Sand
290'	650'	360'	Shale & sandy shale
650'	670'	20'	Shaly sand (Farmington)
670'	1316'	646'	Shale, sandy shale I sand stringers
1316'	1329'	13'	Coal
1329'	1430'	101'	Pictured Cliffs sand
<b><u>ADDITIONAL DATA:</u></b>			
Drill stem test 1337-1448'. Open 3 hours, slight blow throughout.			
Estimated 500 c.f.p.d. of air			
Recovered 20' of mud.			
Cored 1332-1448'; Core analysis furnished separately.			

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Grid with 'X' in the 4th row, 3rd column.

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Benson & Montin

Gallegos Canyon Unit

Well No. 2 in SE/4 of Sec. 35 Lease T. 29N  
R. 12W N. M. P. M. Wildcat Field, San Juan County.  
Well is 3630 feet south of the North line and 3630 feet west of the East line of Section 35  
If State land the oil and gas lease is No. Assignment No.  
If patented land the owner is Unitized - Joe Hartman Address Aztec, N.M.  
If Government land the permittee is Address  
The Lessee is Unitized Address  
Drilling commenced 8-28 19 51 Drilling was completed 9-5 19 51  
Name of drilling contractor M. J. Florance Address Aztec, N.M.  
Elevation above sea level at top of casing 5370 feet.  
The information given is to be kept confidential until Not confidential 19

OIL SANDS OR ZONES

No. 1, from 650 (gas) to 670 No. 4, from to  
No. 2, from 1329 (gas) to 1470 No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from 140 to 210 feet. (Ojo Alamo)  
No. 2 from to feet.  
No. 3, from to feet.  
No. 4 from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
10-3/4	33	8 rd	Nat'l	91'	Common				Surface
8-5/8	32	"	"	262'	"				Shut off Ojo Alamo water

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4	10-3/4	102' (KB)	100	Pump & plug		
10	8-5/8	272 (KB)	100	" "		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	NONE					

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from Surface T.D. feet to feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to producing Temp. abandoned 19  
The production of the first 24 hours was barrels of fluid of which % was oil; %  
emulsion: % water; and % sediment Gravity: Pp