

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Window Rock, Ariz.

Navajo

Allottee Navajo Tract #23

Lease No. 14-20-603-5035

Sec. 36	
T29N R10W	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 29, 19 63

Well No. 1 is located 1900 ft. from N line and 1900 ft. from E line of sec. 36

NW 1/4 Sec. 36
(1/4 Sec. and Sec. No.)

29N
(Twp.)

10W
(Range)

NM
(Meridian)

Pajarito Area
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

RECEIVED

JUL 31 1963

The elevation of the derrick floor above sea level is 5247 ft.

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7/29/63 - 7541' Total Depth: Plugged and Abandoned. Cement plugs spotted in well as follows:
40 Sacks cement from 7400' to 7200' - 200' Plug
75 " " " 6700' - 6350' - 350' "
Perforated 7" csg. at 2500' w/4 holes by McCullough and circulated 11/2 mud thru these perforations and outside of 7" csg., to control water flow and condition hole for pulling 7" csg.. Worked casing and ran McCullough free-point indicator. Found pipe free to 1975' and tight below that point. Cut csg. at 1975' with McCullough Chemical Cutter and pulled same. Spotted 22 sacks cement in 7" csg. from 2590' to 2450' to cover perforations. Spotted 24 sacks cement from 2050' in csg. to 1990' (20' above csg. stub). Left well in condition to be used as water well, as requested by Navajo Tribal Office at Shiprock, New Mexico. Dry-hole marker will be erected and location will be leveled and cleaned. Will file log of well and Schlumberger logs at a later date.


I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353



By D. F. Furse D. F. Furse

Title Foreman

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Window Rock, Ariz.

Navajo

Allottee Navajo Tract #23

Lease No. 14-20-603-5025

Sec. 36		
T29N	R10W	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 29, 1963

Well No. 1 is located 1900 ft. from S line and 1900 ft. from E line of sec. 36

NW 1/4 Sec. 36
(1/4 Sec. and Sec. No.)

29N
(Twp.)

10W
(Range)

NMPS
(Meridian)

Pajarito Area
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

RECEIVED
JUL 31 1963

The elevation of the derrick floor above sea level is 5247 ft.

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7/29/63 - 7541' Total Depth: Flugged and Abandoned. Cement plugs spotted in well as follows:
40 Sacks cement from 7400' to 7300' - 200' Plug
75 " " " 6700' " 6350' - 350' "
Perforated 7" csg. at 2500' w/4 holes by McCullough and circulated 11/2 mud thru these perforations and outside of 7" csg., to control water flow and condition hole for pulling 7" csg.. Worked casing and ran McCullough free-point indicator. Found pipe free to 1975' and tight below that point. Cut csg. at 1975' with McCullough Chemical Cutter and pulled same. Spotted 22 sacks cement in 7" csg. from 2590' to 2450' to cover perforations. Spotted 24 sacks cement from 2050' in csg. to 1950' (20' above csg. stub). Left well in condition to be used as water well, as requested by Navajo Tribal Office at Shiprock, New Mexico. Dry-hole marker will be erected and location will be leveled and cleaned. Will file log of well and Schlumberger logs at a later date.


I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353



By D. F. Furse D. F. Furse

Title Foreman