STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	ator BURLINGTON RESOURCES OIL & GAS CO.							Lease KOCH STATE COM			Well No. 1	
Operator Bl	URLING	SION	RESOURC	ES UIL & GF	13 00.							
Location					T	0001	Rge.	009W	County	SAN JUAN		
of Well:	Unit	G	Sect	36 F RESERVOIR	Twp.	029N		YPE OF PROD.		OD OF PROD.	PROD. MEDIUM	
			NAME O	F KESEKVOIF				(Oil or Gas)	(Flo	w or Art. Lift)	(Thg. or Csg.)	
Upper Completion	PICT	URED	CLIFFS					Gas		Flow Tubing		
Lower Completion	MESAVERDE							Gas	Flow		Tubing	
	L				PRE-	FLOW SHUT-I	N PRES	SURE DATA				
Upper	Hour, date shut-in			Length of	Length of time shut-in			SI press. psig		Stabilized? (Yes or No)		
Completion	9/4/99			120 Hours								
Lower Completion		9/4/99			72 Hours			218				
							TEST NO. 1					
Commenced	at (hou	r.date)*			9/7/99			Zone producing	(Upper or	Lower) LO	WER	
TIME		LAPSED TIME			PRESSURE			PROD. ZONE				
(hour,date)	SINCE*		Upper Co	Upper Completion Lower Comp			TEMP	REMARKS				
9/8/99		96 Hours		16	7	239						
9/9/99	120 Hours		16	165 263		· · · · · · · · · · · · · · · · · · ·						
	-									U	th 27 mg 7	
									12/22/15			
										<u> </u>	Piedla et	
												
Production rat	te during	z test										
Oil:	il: BOPD based on Bbls. in						Hour	s	Grav.		GOR	
						- (Orifina or Mat	tarl:					
Gas:				MCFPD; T	ested thru	ı (Orifice or Met	- LOL).					
					MII	D-TEST SHUT-						
Upper Completion	Hour, date shut-in			Length (Length of time shut-in			press. psig		Stabilized? (\)		
Lower	Hour, date shut-in			Length	Length of time shut-in			SI press. psig			Stabilized? (Yes or No)	

(Continue on reverse side)

			FLOW TEST NO). 2			
Commenced at (hour, d	late)**		Zone producing (Upper or Lower):				
TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE			
(nour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS		
Production rate dur	ring test						
Oil:	BO	PD based on	Bbls. in	Hours	Grav GOR		
I hereby certify that	t the information here	ein contained is true	and complete to the	best of my knowledge			
3	OCT 27			Operator Burlington	Resources		
New Mexico Oil	l Conservation Divis	ion		Alan L	Paus		
Ву	en devide ex	OVERUS T. PERM	1 2	itle Operations Asso	Occiate		
fitle	EPUTY OIL & GAS	INSPECTOR, DIST.	\$ 3	oate Friday, October			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: intractately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).