

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. UNIT AGREEMENT NAME Central Totah	
2. NAME OF OPERATOR Tenneco Oil Company		8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR P.O. Box 3249 Englewood, CO 80155		9. WELL NO. 13	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FNL 430' FEL		10. FIELD AND POOL, OR WILDCAT Totah Gallup	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, ST, CR, etc.) 5446' GL	
		11. SEC., T., R., N., OR B.L. AND SURVEY OR AREA Sec 33 T29N R13W	
		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANE	☐
(Other)	☐		

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
(Other)	☐		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/23/88-- RIH w/ 2-3/8" tbg and 4-1/2" cmt rtnr. Set @ 5164'.

2/24/88-- Circ hole w/ 9.2 mud. Sting into rtnr. Pumped 50 sx (57.5ft³) C1 "B" @ 1700 psi. Sting out. Dumped 30 sx (34.5ft³) of C1 "B" on top of rtnr. Pull to 4067'. Set w/ 157 sx (180.55ft³) plug. Pull to 1440'. Set 20 sx (23ft³) plug. Pull to 1190'. Set 79 sx (90.85ft³) plug. Pull to 172'. Set 14 sx (16.1ft³) plug. Tie onto Bradenhead. Pump 62 sx (71.30ft³) @ 1/2 BPM, 350 psi. SD. (All plugs C1 "B" cmt.) P&A complete.

RECEIVED
BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C.

COPY 10 AM 10:12

WASHINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

Approved for release by the
Under Secretary of the Interior
Surface Reclamation Division, BLM

RECEIVED
MAR 2 8 1988
OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Sr. Administrative Analyst

DATE 3/10/88

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

MAR 22 1988
DATE

*See Instructions on Reverse Side