

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
FLM RIDGE RESOURCES, INC.

3. Address and Telephone No.
4925 GREEVILLE AVE., STE 1305 DALLAS, TX 75206 (214) 696-8090

4. Location of Well (Footage, Sec., T., R., N., or Survey Description)
990' FSL, 990' FWL
SEC. 28, T29N, R13W

5. Lease Designation and Serial No.
NMMV - 0468126

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
CALLOW #4-

9. API Well No.
3304507796

10. Field and Pool, or Exploratory Area
W. KUTZ P.C.

11. County or Parish, State
SAN JUAN, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
<input checked="" type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other: _____	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on W.C. Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PLUG AND ABANDON WELL PER PROCEDURES ATTACHED).

WELLBORE DIAGRAMS ATTACHED.



200 JUL 25 PM 12:17
OIL CON. DIV

14. I hereby certify that the foregoing is true and correct

Signed

David L. Lively

Title

OPERATIONS MANAGER

Date

7/20/2000

(This space for Federal or State office use)

Approved by

Title

Date

8/2/00

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

* See Instruction on Reverse Side

PLUG AND ABANDONMENT PROCEDURE

CALLOW #4
PICTURED CLIFFS
SEC. 28, T28N, R13W
SAN JUAN, NEW MEXICO

NOTE: ALL CEMENT VOLUMES USE 100% EXCESS OUTSIDE PIPE AND 50 FT. EXCESS INSIDE PIPE. THE STABILIZING WELLBORE FLUID WILL BE 8.3 ppg, SUFFICIENT TO BALANCE ALL EXPOSED FORMATION PRESSURES.

1. INSTALL AND TEST RIG ANCHORS. PREPARE BLOW PIT. COMPLY TO ALL BLM, ELM RIDGE, AND KEY ENERGY SAFETY RULES AND REGULATIONS. MOL AND RU DAYLIGHT PULLING UNIT AND PLUGGING EQUIPMENT. CONDUCT SAFETY MEETING FOR ALL PERSONNEL ON LOCATION. NU RELIEF LINE TO BLOW DOWN WELL. KILL WITH WATER AS NECESSARY. ND WELLHEAD AND NU BOP, TEST BOP.
2. PLUG #1 (PICTURED CLIFFS, 1500' - 1543'): POH AND LD 1553' OF 1 1/2" TUBING. RU WIRELINE UNIT AND RIH WITH 5 1/2" GAUGE RING TO 1543'. POH. RU AND RIH WITH 5 1/2" CIBP AND SET AT 1543'. PU 2 3/8" WORK STRING AND TAG TOP OF CIBP. CIRCULATE HOLE CLEAN WITH WATER AND PRESSURE TEST CASING TO 500 PSI. BALANCE 11 SX CL. B CEMENT PLUG ON TOP OF CIBP AND POH.
3. PLUG #2 (FRUITLAND, 655' - 755'): RIH WITH WIRELINE AND PERFORATE 3 SQUEEZE HOLES AT 755'. POH. PU AND RIH WITH 5 1/2" RETAINER AND SET AT 705'. ESTABLISH INFILTRATION RATE INTO PERFORATIONS WITH WATER. MIX 47 SX CL. B CEMENT PLUG, PLACING 36 SX BELOW AND 11 SX ABOVE RETAINER. POH.
4. PLUG #3 (SURFACE, 0' - 153'): RIH WITH WIRELINE AND PERFORATE 2 SQUEEZE HOLES AT 153'. ESTABLISH CIRCULATION TO SURFACE OUT THE BRADON HEAD WITH WATER. MIX APPROXIMATELY 49 SX CL. B CEMENT TO CIRCULATE GOOD CEMENT TO SURFACE.
5. ND BOP AND DIG CELLAR. CUT OFF WELLHEAD 3' BELOW GROUND LEVEL. TOP OFF CASING AS NEEDED. RIG DOWN RIG AND CUT OFF RIG ANCHORS. INSTALL DRY HOLE MARKER AND MOL. RECLAIM LOCATIONS AS PER BLM REQUIREMENTS.

Nathan Crawford
NATHAN CRAWFORD
P&A SUPERVISOR

CALLOW #4
CURRENT
SEC. 28, T29N, R13W
SAN JUAN, NM
PICTURED CLIFFS

TODAYS DATE: 07-18-00

SHOE @ 103'

13" OH

8 5/8", 24#, @ 103', CMT W/ 80 SX. CIRCULATED

1 1/2" @ 1553'

FRUITLAND @ 705'

7 7/8" OH

TOC @ 1048' CALCULATED W/ 75% FILL

PICTURED CLIFFS @ 1550'

5 1/2", 14# SET @ 1553'
CMT W/ 100 SX

4 3/4" OH COMPLETED TO 1576'

CALLOW #4
PURPOSED
SEC. 28, T29N, R13W
SAN JUAN, NM
PICTURED CLIFFS

TODAYS DATE: 07-18-00

SHOE @ 103'

PLUG #3 (0' - 153'), CMT W/ 45 SX

13" OH

8 5/8", 24# @ 133' CMT W/ 60 SX. CIRCULATED

PERFORATE @ 153'

7 7/8" OH

PLUG #2 (655' - 755'), CMT W/ 47 SX

RETAINER @ 705'

PERFORATE @ 755'

TOC @ 1048' CALCULATED W/ 75% FILL

PLUG #1 (1500' - 1543'), CMT W/ 11 SX

CIBP @ 1543

5 1/2", 14# SET @ 1553'

CMT W/ 100 SX

4 3/4" OH COMPLETED TO 1575'

ERUITLAND @ 705'

PICTURED CLIFFS @ 1553'

