## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

L001			<u> </u>	FO	rmation		Pareta		_county	Jee Jus		
Init	ial	<u>x</u>	Annua	L		Spec	ial		_Date of T	est	3-6-64	
Comp	any Mi	MORR TOA	PETROL	ETM CO	<b>127.</b>	Lease	torrio Ge	o Vait "	Well	No	1	
Unit	<u> </u>	_Sec	Twp.	29N	Rge	. <u>100</u>	Purc	haser		<u></u>		
Casi	ng 4-1/2	Wt1	9.5 I.I	. <b>4.</b>	<b>25</b> Se	t at	12 Pe	rf. 629	5-6300 7	o_ 631	7-6331	
Tubi	ng 2-3/8		6.7 I.I	1.9	<b>95</b> Set	t at	Pe:	rf	Open	Inded	····	
Gas	Pay: Fro	m 6295	To <b>63</b>	31	_L_631	3x	G .700		4419 E	ar.Pres	s	
Prod	ucing Thr	u: Ca	sing		Tul	oi.ng	X	Type We	11	ingle		
							Sin	gle-Brade	nhe <b>sd-G.</b> G	. or G.	O. Dual	
	-	-			<del></del>		ED DATA	<del></del>				
reet.	ed Throug	h (Bar	) (C)	noke)	(Madaaa)				Type Taps	. 71		
			Flow Dat		7		Tubing	·Do+a	Casing Da			
T	(Prover	) (Ch	oke) I		Diff.	Temp.		Temp.	Press.	Temp.	Duration	
No.	(Line) Size	(Ori	fice) Size	psig	h <sub>w</sub>	°F.	psig	°F.	psig	or.	of Flow Hr.	
SI	7 447						2004		2004			
L.	2 incl	. 0	.375	244			264	600 00	. 569	60° est	3 hgs.	
2 <b>.</b> 3 <b>.</b>	<del></del>		+						<u> </u>	<del></del>	<u></u>	
4.												
5.								L				
					1	LOW CAL	CULATION	S				
T	Coefficient			Pressure Flow Temp			Temp.	Gravity Compress. Rate of Flow				
Vo.	(0) 11)		7	-		Fac	tor	Factor	Factor		Q-MCFPD	
_		(24-Hour)		·	psia	Ft		Fg	Fpv		@ 15.025 psia	
2.	12.3650				256	1.000		9258	1.031		<u> </u>	
3.												
2.	·	<del></del>	J									
	iquid Hyd ty of Liq		rocarbor	ıs_		ESSURE C. cf/bbldeg.	alcui ati	Speci	fic Gravit fic Gravit	y Flowi	ng Fluid	
:			(1-	-e <sup>-8</sup> )				P <sub>c</sub>	2916	Pc	,064,236	
	P <sub>w</sub>							<del></del>	<u> </u>	1	<del>-  </del>	
No.	Pt (psia	) F	$\frac{2}{t}$ $F_c$	ı	$(F_cQ)^2$	(F	$\frac{c^{Q}}{-e^{-s}}$	$P_{\mathbf{w}}^2$	$P_c^2 - P_w^2$	Cal.		
.+	TC (berg						- 1	336,460	3,727,83	, w		
2.												
3. ]							<del></del>			<del> </del>		
5.+	<del> </del>											
	lute Pote			3223		MCFPD;	n	.75				
COMP ADDR			Versia			igo	<del></del>					
AGEN	T and TIT		1 / C	1/5	TVIII					CCII		
	ESSED		7. 7.	Pooli						<del>311/1</del> 1	1	
COMP	ANI					REM	ARKS	·	<del></del>	- 4 (	3 1964	
	-								-	MAR1		

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure  $(P_W)$ . MCF/da. @ 15.025 psia and 60° F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_f$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- $F_g$ : Gravity correction factor.
- Ft Flowing temperature correction factor.
- F<sub>DV</sub> Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .