

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO. 3004507867

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention

Pat Archuleta

P.O. Box 800 Denver Colorado 80201 303-830-5217

7. Lease Name or Unit Agreement Name

Mc Daniel Gas Com B

8. Well No.

#1

9. Pool name or Wildcat

Basin Dakota

4. Well Location

Unit Letter H : 1850 Feet From The NORTH Line and 1190 Feet From The EAST Line

Section 26 Township 29N Range 10W NMPM SAN JUAN County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details and give payment dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 9/24/97.

Set CIBP at 6252', load and test csg to 500# for 15 min. Held okay.

Spot cmt plug inside csg from 6258'-6108' w/11 sxs CI-B cement.

Spot cmt plug inside csg from 5408'-5258' w/11 sxs CI-B cement.

Spot cmt plug inside csg from 3735'-3585' w/11 sxs C-B cement.

Spot cmt plug inside csg from 2914'-2764' w/11 sxs CI-B cement.

Spot cmt plug inside csg from 1903'-1440' w/31 sxs CI-B cement.

Spot cmt plug inside csg from 924' to surface w/69 sxs CI-B cement, cut off wellhead, fill csgs to surface, install marker.

RDMOSU 9/26/97

RECEIVED  
MAR - 2 1998

OIL CON. DIV.  
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Pat Archuleta*

TITLE

Staff Assistant

DATE

10-03-1997

TYPE OR PRINT NAME

Pat Archuleta

TELEPHONE NO.

303-830-5217

(This space for State

APPROVED BY

*Ray Smith*

TITLE

*Field Rep I*

DATE

5-6-98

CONDITIONS OF APPROVAL, IF ANY: