Form	<b>n 9-3</b> pril 19 <i>8</i>	31 b	À,	TEIL
	-{ }		KL	PLIAFD/
X			AU	G 2 5 1960 E
		0	IL.	CON. COM.
		/		DIST 3

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES**

EPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY** 

Indian Agenty 20-603-2172	<u>:</u>
Allettee	-

_pist. 3	े व	<u>_</u> @	e 1	W	F	m
DIST. 3 SUNDRY NOTICES AND REPORTS ON	TATELLE			Ų.	طا	
SUNDKI NUTICES AND REPURTS ON	AA TITIE	7				

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS.	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING URVEY SUBSEQUENT REPORT OF ALTERING CASING U. S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING U.S. GEOLOGICAL CONTROL OF ALTERING U.S. GEOLOGICAL CONTROL OF ALTERING CASING U.S. GEOLOGICAL CONTROL OF ALTERING U.S. GEOLOGICAL CONTROL OF ALTERING U.S. GEOLOGICA CONTROL OF ALTERING U.S
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING II S. GEOLUGICAL GEOLUGICA GEOLUGIC
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING.	BERTHENDAMINH HIS OPERations
NOTICE OF INTENTION TO ABANDON WELL	A A

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

NAVAJO TRIBE	OF	INDIANS	uL'11
--------------	----	---------	-------

HOBBS, NEW MEXICO, AUGUST 22, 1960

Well No is	located 980 ft	. from $\{N\}$ line	e and $\frac{660}{\text{ft. from}} \text{ft. from} \left\{ \begin{array}{c} X E \\ W \end{array} \right\}$ line of sec. $\frac{26}{\text{c}}$			
SW/4 OF NW/4 26	29N	14W				
(14 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)			
OJO GALLUP	SAN	JUAN	NEW MEXICO			
(Field)	(C	ounty or Subdivision)	) (State or Territory)	(State or Territory)		

The elevation of the derrick floor above sea level is LATER ft.

## **DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment-ing points, and all other important proposed work)

Spudded 11" hole at 7:30 P.M. 8-8-60. Ran 207' (5 Jts) 7-5/8" 26.4 J-55 casing set at 219'. Cement with 140 sacks Reg neat cement with 2% cal chloride. Cement circulated. Tested casing with 1000# for 30 min- no drop in pressure. Drilling.

Address OPIGINAL ARVIN D. EADY  BOX 2347  HOBBS, NEW MEXICO  By SIGNED: ARVIN D. EADY	I understand that this plan of work must receive approval in writing by HUMBLE OIL & REFINING COMPANY Company		Survey before oper	ations may be commenced.
By SIGNED. AKVIN D. EADY	Address		OPIGINAL	100/04 p.
Title_AGENT	HOBBS, NEW MEATCO	•		ARVIN D. EADY