

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan
Initial X Annual _____ Special _____ Date of Test 9-17-63
Company Pan American Petroleum Corporation Lease Norton Gas Unit Well No. 1
Unit A Sec. 20 Twp. 29-N Rge. 11-W Purchaser _____
Casing 4 1/2 Wt. 10.5 I.D. 4.090 Set at 6181 Perf. 6110 To 6125
Tubing 2 1/8 Wt. 3.25 I.D. 1.790 Set at 5961 Perf. - To -
Gas Pay: From 6110 To 6125 L 6118 xG .700 est GL _____ Bar.Press. 12
Producing Thru: Casing _____ Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. Dual _____
Date of Completion: 9-10-63 Packer None Reservoir Temp. _____

OBSERVED DATA

Tested Through ROCKET (Choke) ROCKET Type Taps Flange

Flow Data						Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
1.	<u>7 Days</u>	<u>.750</u>	<u>309</u>			<u>2039</u>		<u>2014</u>		<u>3 hours</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.3630</u>		<u>401</u>	<u>1.0000</u>	<u>.9250</u>	<u>1.030</u>	<u>4320</u>
2.							
3.							
4.							
5.							


PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
F_c _____ (1-e^{-s})
Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 2036 P_c 1277.136

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	(1101) P _c ² 1,304,701	P _c ² -P _w ² 2632375	Cal. P _w	P _w P _c
1.									
2.									
3.									
4.									
5.									

Absolute Potential: 6908 MCFPD; n 0.75
COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS Box 480
AGENT and TITLE P. W. Poell
WITNESSED _____
COMPANY _____

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .