

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Include instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-603-2199

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

NW Cha Cha

8. FARM OR LEASE NAME

NW Cha Cha Unit

9. WELL NO.

32-22

10. FIELD AND POOL, OR WILDCAT

Cha Cha Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22-29N-14W MNPM

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Water Injection Well

2. NAME OF OPERATOR
Humble Oil & Refining Company

3. ADDRESS OF OPERATOR
P. O. Box 120, Denver, Colorado 80201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

SW NE (1830' FNL, 1830' FEL) of Sec. 22

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5288' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-15-72 Squeeze 4½" x 8 5/8" annulus with 35 sxs

9-26-72 Unable to pump into perfs @ 4886-91.

11-2-72 Set McCullough bridge plug in 2 3/8" tbs @ 4000'.

Spot 10 sxs cement 400' to 0'.

Intervals between plugs filled with gelled mud.

Installed regulation dry hole marker and cleaned location for inspection.

CC: 2-New Mexico Oil Conservation Commission
1-Minerals Supervisor-Navajo Tribe
1-Midland



18. I hereby certify that the foregoing is true and correct

SIGNED J. Roy Dorrrough

TITLE District Superintendent

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side