

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

I-68-IND-38

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Savage Tribal

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Section 18

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Magbana Subota

11. SEC. T., R., M., OR BLM. AND

**34/4 25/4 Section 18,
T-29-N, R-16-W**

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | |
| 2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION | |
| 3. ADDRESS OF OPERATOR 301 Airport Drive, Farmington, New Mexico 87401 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 2310' FSL, Section 18, T-29-N, R-16-W | |
| 14. PERMIT NO. | 15. ELEVATIONS (Show whether DF, RT, GR, etc.) |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**The subject well was cleaned out and drilled 1-1/2' deeper to a TD of 486'. A
Lyness packer was set at 483'. The well then flow tested 36 BOPD and 145 BWFS.**



RECEIVED

MAR 15 1968

U. S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

G. W. Sutton, Jr.

TITLE

Area Engineer

DATE

March 14, 1968

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side