
Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form App		
Land Office	Santa	Fe
Lease No.	077092	
u s/2		

Budget Bureau No. 42-R358.4.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		
	xxx	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE P	LANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATE	ER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL	OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR 1.1 1063
NOTICE OF INTENTION TO SHOOT OR	ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT JUN 10 1000
NOTICE OF INTENTION TO PULL OR A	LTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON	WELL	U. S. GEOLOGICAL SURVE
		U. S. GEOLOGI, NEW MEXTO
(INDICAT	TE ABOVE BY CHECK MARK NAT	URE OF REPORT, NOTICE, OR OTHER DATA)
		June 7, 1963 , 19
J. Glenn Turner -		, , , , , , , , , , , , , , , , , , ,
	ed 790 ft. from [$\frac{11}{3}$ line and 840 ft. from $\frac{E}{4}$ line of sec. 11
SE/4 Section 11 (½ Sec. and Sec. No.)	T 29-N R	- 10-W N.M.P.M. (Meridian)
(½ Sec. and Sec. No.)	(Twp.) (Ran	ge) (Meridian)
Basin Dakota		
(Field)	(County or Sub	division) New Maxico (State or Territory) UNI 1 196
he elevation of the derrick	floor above sea level i	s 5.79lft. 01 034
	DETAILS	OF WORK
itate names of and expected depths to	objective sands; show sizes, we	sights, and lengths of proposed casings; indicate mudding jobs, costen
	ing points, and all other	mportant proposed work)
SOUTH		200
SeytH akota Test. North hal	f of Section 11 (320 acres) dedicated to the well.
akota Test. North half asing Program: Drilli that point. Cen Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial producter fractured, and 2-	ing 12-1/4" hole to the to surface with to total depth of a; cement with 220 to 100 sacks 4-1/29 rde. The cliffs with 75 sacks total indicated, 3/8" tubing will	th approximately 200 sacks neat cement. approximately 7,000 feet. Set sacks cement, 16% gel, with 64% gel. This amount of cement should acks cement, 4% gel. well will be perforated, sand be set for production purposes.
akota Test. North half asing Program: Drilli that point. Cem Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial product fractured, and 2-	ing 12-1/4" hole to the to surface with to total depth of a; cement with 220 to 100 sacks 4-1/29 rde. The cliffs with 75 sacks total indicated, 3/8" tubing will	th approximately 200 sacks neat cement. approximately 7,000 feet. Set sacks cement, 16% gel, with 6½% gel. This amount of cement should afts - approximately 2400 feet - and tacks cement, 4% gel. well will be perforated, sand
akota Test. North half asing Program: Drilli that point. Cem Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial producter fractured, and 2- I understand that this plan of work	ing 12-1/4" hole to the to surface with to total depth of a; cement with 220 to 100 sacks 4-1/29 rde. Delow Pictured Cliff Cliffs with 75 shuction indicated, 3/8" tubing will must receive approval in writing	to 300 feet - set 8-5/8" casing at the approximately 200 sacks neat cement. The approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and tacks cement, 4% gel. Well will be perforated, sand be set for production purposes. The production purposes in the Geological Survey before operations may be commenced.
akota Test. North half asing Program: Drilli that point. Cen Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial producter fractured, and 2-	ing 12-1/4" hole to the to surface with to total depth of a; cement with 220 to 100 sacks 4-1/29 rde. Delow Pictured Cliff Cliffs with 75 shuction indicated, 3/8" tubing will must receive approval in writing	to 300 feet - set 8-5/8" casing at the approximately 200 sacks neat cement. The approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and tacks cement, 4% gel. Well will be perforated, sand be set for production purposes. The production purposes in the Geological Survey before operations may be commenced.
akota Test. North half asing Program: Drilli that point. Cem Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial producer fractured, and 2- I understand that this plan of work company J. Glenn Tu	ing 12-1/4" hole to tent to surface wing to total depth of a; cement with 220 a 100 sacks 4-1/29 and a 100 sacks 4	to 300 feet - set 8-5/8" casing at the approximately 200 sacks neat cement. The approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and tacks cement, 4% gel. Well will be perforated, sand be set for production purposes. The production purposes in the Geological Survey before operations may be commenced.
akota Test. North half asing Program: Drilli that point. Cem Drill 7-7/8" hole -1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage to ement off the Pictured If commercial producter fractured, and 2- I understand that this plan of work	ing 12-1/4" hole to tent to surface wing to total depth of a; cement with 220 a 100 sacks 4-1/29 and a 100 sacks 4	to 300 feet - set 8-5/8" casing at the approximately 200 sacks neat cement. The approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and tacks cement, 4% gel. Well will be perforated, sand be set for production purposes. The production purposes in the Geological Survey before operations may be commenced.
akota Test. North hale asing Program: Drilli that point. Cem Drill 7-7/8" hole 1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collage the ment off the Pictured If commercial producter fractured, and 2-1 understand that this plan of work fompany J. Glenn Tu	ing 12-1/4" hole to tent to surface wing to total depth of a; cement with 220 to 100 sacks 4-1/2% rde. The color of the co	th approximately 200 sacks neat cement. approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and sacks cement, 4% gel. well will be perforated, sand be set for production purposes. In a same of the same of
akota Test. North half asing Program: Drilli that point. Cen Drill 7-7/8" hole 1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collate the ment off the Pictured If commercial producer fractured, and 2-1 understand that this plan of work tompany J. Glenn Tuddress P.O. Box 728	ing 12-1/4" hole to tent to surface wing to total depth of a; cement with 220 to 100 sacks 4-1/2% rde. The color of the co	to 300 feet - set 8-5/8" casing at the approximately 200 sacks neat cement. The approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and tacks cement, 4% gel. Well will be perforated, sand be set for production purposes. The production purposes in the Geological Survey before operations may be commenced.
akota Test. North half asing Program: Drilli that point. Cen Drill 7-7/8" hole 1/2" casing on bottom ilsonite per sack, and ement off the Mesa Ver Set stage collate tement off the Pictured If commercial producer fractured, and 2-1 understand that this plan of work company J. Glenn Tuddress P.O. Box 728	ing 12-1/4" hole to tent to surface wing to total depth of a; cement with 220 to 100 sacks 4-1/2% rde. The color of the co	th approximately 200 sacks neat cement. approximately 7,000 feet. Set sacks cement, 16% gel, with 61% gel. This amount of cement should affs - approximately 2400 feet - and sacks cement, 4% gel. well will be perforated, sand be set for production purposes. In a same of the same of

NEW MEXICO OIL CONSERVATION COMMISSION

Well Location and Acreage Dedication Plat

Operator J. GLENN TURNER Well No. 1-11 Unit Letter Located 790 Feet Fr County SAN JUAN	P com the SOU	TH Line	11 5784.	840	Townshi Dedicat	Feet Fr ted Acre	om	the E	10 WEST AST 220	L in e
Name of Producing Formation		ated acrea					<u> </u>			
YesNo					•					
2. If the answer to question one agreement or otherwise? Yes										itizatio
3. If the answer to question two	is "no", lis	t all the	owners	and their	respect	ive inte	rests be	low:		
Owner	*				La	nd Des	cription	F	EFF	M
								<i>'</i> J	UNII	TO
								OIL	CON. C	OM.
Section B.		Note:	All dis	tances m	ust be f	rom oute	er bounde	No. of the last		
•						1		T	Section.	1
This is to certify that the information in Section A above is true and co					+ 1				. -	
to the best of my knowledge and			τ -			+ - -	<u> </u>		-	
2. Mayer Starger							1 1		;	
polly on		-				+-:	· I .		1	
(Representative)					'	-	i		1	
(Address)	· •				4.5		· · · · ·		1	
Personage to a live lives	.00		· · · - ·	:	1	11	**************************************			
V.			F. 07	1090-C	· •		2. OF		\$ 62 cm . \$2 g	N
Ref: GLO plat dated 19 App	ril 1881				a Ange		* . I		- I I I I I I I I I I I I I I I I I I I	
•				ļ.,	i	+	1	ļ	1	
					ne de la companya de La companya de la co	: {	1		- I	
	*		.	1	1-12 - 12	ļ	1	•	840	
			<u>.</u>		i			,061	1	
						-			4	
		0 333 6	60 990 1	320 1650 1	980 2310	2640 2	000 1500	1000	500 0)
				Scale	4 inche	launa se	1 mile			

This is to certify that the above plat was prepared from field notes of actual surveys made by me or under my supervision and that the same are true and correct to the best of my knowledge and belief.

Registered Professional Engineer and/or Land Surveyor James P. Leese, N. Mex. Reg. No. 1463

Farmington, New Mexico