

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

1-89-IND-56

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rattlesnake Gov't.

9. WELL NO.

142

10. FIELD AND POOL, OR WILDCAT

Rattlesnake - Penn. BCD

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 12, T29N, R19W

12. COUNTY OR PARISH

13. STATE
San Juan New Mexico

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

152 North Durbin, Casper, Wyo. 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL, 1980' FWL (Unit Letter F)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5389' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Well History: TD 6816'. 13 3/8" surface casing, 48", H-40 set at 320' and 9 5/8" intermediate casing, 36#, J-55 set at 4650'. Production casing, 7", 23#, J-55 set at 6688'. Open-hole 6688-6816'. Well Status: Oil temporarily shut-in.

We propose to plug the well as follows:

~~Spot 20-sack cement plug 6420-6520'.~~~~Spot 25' plug in surface casing.~~

Set 10' length of 4" pipe in surface plug so that it projects at least 4' above the ground level.

Top of 4" will be capped and a marker attached or welded on pipe.

200' cement plug 6400-6600'

150' " " 5575-5700'

100' " " 4300-4400'

30' surface plug with marker.

USGS(6) NMOGCC(2) File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

Elmer L. Phillips

TITLE Administrative Supervisor

DATE 8-18-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side