

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FNL & 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

5. LEASE
SF-076958

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Hare

9. WELL NO.
#2

10. FIELD OR WILDCAT NAME
Blanco Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 3, T29N, R10W

12. COUNTY OR PARISH | 13. STATE
San Juan | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5867' KB

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) _____

SUBSEQUENT REPORT OF:

RECEIVED
DEC 24 1982
U.S. GEOLOGICAL SURVEY

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-13-82 Set cement retainer at 2258', pumped into perms.

12-14-82 Squeezed Pictured Cliffs perms with 30 sacks Class "B" cement. Dumped 5 sacks cement on top of retainer. Spotted 15 sacks cement plug from 1980'-1880'. Shot squeeze holes at 1255'. Squeezed with 68 sacks Class "B" cement. Left cement inside and outside casing from 1255'-1060'. Perfd squeeze hole at 150'. Pumped 50 sacks cement, cut off well head, installed dry hole marker with 10 sacks cement. Cleaned up location.

AUG 01 1984
OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Secretary DATE December 21, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 30 1984
M. MILLENBACH

*See Instructions on Reverse Side

M. MILLENBACH
AREA MANAGER

NMOCC