



(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Indian Agency

Navajo Tribal

Allottee

Lease No. 14-20-60-2177

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

Navajo Tribal "F"

Farmington, New Mexico November 29, 1960

Well No. 6 is located 400 ft. from [S] line and 1200 ft. from [E] line of sec. 22

SW/4 SE/4 of Section 22
(1/4 Sec. and Sec. No.)T-22-N
(Twp.)R-14-W
(Range)N.M.P.M.
(Meridian)Undesignated Gallup
(Field)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 5400 ft. (CL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 12-1/4" hole on November 15, 1960 and drilled to 202'. Set 8-5/8" casing at 202' with 160 sacks cement containing 2% calcium chloride. Circulated 15 sacks of cement. After waiting on cement, tested 8-5/8" casing with 500 psi for 30 minutes, which held with no indication of pressure drop. Reduced hole to 7-7/8" at 202' and resumed drilling operations.

Total depth 5405'. Set 4-1/2" casing at 5405' with 175 sacks 6% gal cement with 1-1/2 pounds medium Taf Plug per sack followed by 75 sacks neat cement. Pumped plug down with 300 gallons 1% NEA with oil. Tested casing with 3000 psi for 10 minutes which held with no indication of pressure drop. Released rotary rig November 27, 1960. Preparing for completion operations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 400

Farmington, New Mexico

Attn: L. O. Spear, Jr.

ORIGINAL SIGNED BY
R. M. Bauer, Jr.

By

Area Engineer

DEC 5 1961