


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



Budget Bureau No. 42-R358.4.
Form Approved.

Land Office Santa Fe
Lease No. 078580-A
Unit E 1/2 Sec 5

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 19 1963

Well No. Moore 6 is located 1135 ft. from [N] line and 1090 ft. from [E] line of sec. 5

NE 1/4 Sec. 5 T-30-M R-8-W N 1/2 PM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Basin Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6274 ft. G. L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 6 3/4" hole below 7 5/8" casing to T. D. of 7750'. Ran 215 Jts. of 5 1/2 15.5# J-55 casing landed 6933: Baker TC collar @ 5841 cemented 1st. stage w/38 sks pozmix--opened TC collar 2nd. stage w/82 sks Class C cement. Recemented w/400 cu. ft. Diacel "D" cement. Ran 35 jts. of 4 1/2 10.50# J-55 casing liner landed 7741' (Top of Liner @ 6648') cemented w/250 cu. ft. Pozmix. Cemented 10 3/4" and 5 1/2 annulus w/70 sks Class C cement.

(over)
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Delhi-Taylor Oil Corp.

Address P. O. Box 1198

Farmington, N. M.

Original signed by
By A. R. Gibson
Title A. R. Gibson
Dist. Supt.

Cement tops from Cement Bond Log as follows:

5 1/2" casing above 4400'

Log only goes to 4400'

4 1/2" Liner 6648 (Entire liner bonded)

Now waiting on completion rig.