

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

1000771 N. 15.4
070 FARMINGTON, NM

Lease Number
SF-078197
If Indian, All. or
Tribe Name

2. Name of Operator

**BURLINGTON
RESOURCES** OIL & GAS COMPANY

7. Unit Agreement Name

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
Nye #5

9. API Well No.
30-045-20788

4. Location of Well, Footage, Sec., T, R, M

990' FSL, 1090' FWL, Sec.9, T-29-N, R-10-W, NMPM

10. Field and Pool
Aztec Pictured Cliffs

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment

Type of Action

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to plug and abandon the subject well according to the attached procedure and wellbore diagram. Please cancel our sundry to test casing integrity approved 6-14-95.

RECEIVED
OCT 23 1995
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] (KM2) Title Regulatory Administrator Date 10/9/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____
CONDITION OF APPROVAL, if any:

Day **APPROVED**

OCT 17 1995
for Chip Haraden
DISTRICT MANAGER

PLUG & ABANDONMENT PROCEDURE

NYE #5

Aztec Pictured Cliffs

DPNO: 52411A

990' FSL, 1090' FWL

Unit M, Sec. 9, T29N, R10W

Longitude/Latitude: 107.895279 - 36.735916

Note: All cement volumes use 100% excess outside pipe and 50' excess inside pipe. The stabilizing wellbore fluid will be 8.3 ppg, sufficient to balance all exposed formation pressures.

1. Install and test location rig anchors. Prepare blow pit. Comply to all NMOCD, BLM, and BROG safety regulations.
2. MOL and RU daylight pulling unit. Conduct safety meeting for all personnel on location. NU relief line. Blow down well and kill with water as necessary. ND wellhead and NU BOP. Test BOP.
3. **Plug #1 (Pictured Cliffs perms and Fruitland tops, 2026' - 1826')**: RIH and tag CIBP. PU 2024' of 1-1/4" tubing and RIH to 2024' or as deep as possible. Mix and pump 9 sxs Class B cement and spot a balanced plug above the bridge plug. PUH to 1116'
4. **Plug #2 (Kirtland and Ojo Alamo tops, 1116' - 914')**: Mix and pump approximately 7 sxs Class B cement and spot a balanced plug to cover the Ojo Alamo top. POOH
5. **Plug #3 (192' - Surface)**: Perforate 2 holes @ 192'. Establish circulation out bradenhead valve. Mix and pump approximately 62 sxs Class B cement down 2-7/8" casing, circulate good cement out bradenhead valve. Shut in well and WOC.
6. ND BOP and cut off wellhead below surface casing. Note the cement level in the casing and annulus; fill as necessary. Install P&A marker to comply with regulations.
7. Rig down, cut off anchors, move off location, and restore location per BLM stipulations.

Recommended:

Kevin L. Midkiff 10/8/96
Operations Engineer

Approval:

Production Superintendent

Operations Engineer:

Kevin Midkiff

326-9807

564-1653 (Pager)

Nye #5

DPNO: 52411A

CURRENT 10/2/96

Spud: 6/4/71
Completed: 6/22/71
Workover: 12/71 - Install tbg.
and BOP
5/95 - Cleanout
6/95 - Set BP
Elev.: 5797' KB
5786' GL

Aztec Pictured Cliffs

990' FSL, 1090' FWL

Unit M, Sec. 9, T29N, R10W, San Juan County

Lat / Long: 107.895279 - 36.735916

12-1/4" Hole

8-5/8", 24#, K55 csg. set @ 142'
Cmt. w/90 sxs Class A. Circulate to surface

Ojo Alamo @ 964'

TOC @ 800' (TS)

Kirtland @ 1066'

Fruitland Coal @ 1876'

Pictured Cliffs @ 2178'

6/6/95: Bridge plug set @ 2026'

Perfs @ 2180' - 2200' - 60 Holes - 3 SPF
Frac w/30,000# 10/20 sand, 33,900 gal.
water.

6-3/4" Hole

2-7/8", 6.4#, J55 csg. set @ 2285'
Cmt. w/175 sxs Class C, 50 sxs Neat

COTD 2275'

TD 2285'

Nye #5

DPNO: 52411A

Proposed P&A

Spud: 6/4/71
Completed: 6/22/71
Workover: 12/71 - Install tbg.
and BOP
5/95 - Cleanout
6/95 - Set BP
Elev.: 5797' KB
5786' GL

Aztec Pictured Cliffs

990' FSL, 1090' FWL

Unit M, Sec. 9, T29N, R10W, San Juan County

Lat / Long: 107.895279 - 36.735916

12-1/4" Hole

8-5/8", 24#, K55 csg. set @ 142'
Cmt. w/90 sxs Class A. Circulate to surface

Plug #3: 192' - Surface
Perf 2 holes @ 192'
Cmt. w/62 sxs Class B

TOC @ 800' (TS)

Plug #2: 1116' - 914'
Cmt. w/7 sxs Class B

Ojo Alamo @ 964'

Kirtland @ 1066'

Fruitland Coal @ 1876'

Plug #1: 2026' - 1826'
Cmt. w/9 sxs Class B

6/6/95: Bridge plug set @ 2026'

Pictured Cliffs @ 2178'

Perfs @ 2180' - 2200' - 60 Holes - 3 SPF
Frac w/30,000# 10/20 sand, 33,900 gal.
water.

6-3/4" Hole

2-7/8", 6.4#, J55 csg. set @ 2285'
Cmt. w/175 sxs Class C, 50 sxs Neat

COTD 2275'

TD 2285'

