

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Walter Duncan

3. ADDRESS OF OPERATOR
Box 234, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
2400' FSL -- 2350' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4982' GR

5. LEASE DESIGNATION AND SERIAL NO.
14-20-0603-9591

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
North Hogback 1

9. WELL NO.
19

10. FIELD AND POOL, OR WILDCAT
Slickrock - Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1, T29N, R17W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Millikin Drilling Company drove 7" csg to 18', drilled 5' below csg, and cemented 7" csg with 5 sx.

4-20-75

Finished drilling 6-1/4" hole to 658' with water. Ran electric log by Go International - logger's TD 658'. Ran 19 jts 4-1/2" OD 9.5# 8R ST&C IPSCO KCW new csg. TE 668.77' set at 658' GR cemented by HOWCO with 75 sx Class "B" - bumped plug with 700 psi. POB 3:30 PM 4-19-75.

4-22-75

Cut off 4-1/2" csg and welded on 4-1/2" slip on coupling. Picked up 2-3/8" tbg and blew down hole. Drilled cementing plug and csg shoe and dried hole. Drilled a total of 12' of hole below csg shoe (7' with no show and 5' pay section - blowing free oil from hole last 4'). Pulled 3-7/8" bit and ran 21 jts 2-3/8" OD 4.7# 8R EUE "B" condition csg. TE 659.20' set at 658' GR. Note: TD is 670'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

4-25-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side