

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

14-20-0603-10008

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

North Hogback 6

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Slickrock - Dakota

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec 6, T29N, R16W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1. OIL ☒ GAS ☐  
WELL WELL OTHER

2. NAME OF OPERATOR

Walter Duncan

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

2146' FSL - 924' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5002' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐Completion ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*2-24-76

Finished drilling 6-1/4" hole to 684'. Ran GO International electric log and ran 21 jts 4-1/2" OD 9.5# 8R ST&C csg, TE 684.81' set @ 684' GR, cemented w/75 sx Class "B" neat, good mud returns while cementing - cement circulated. Max cementing press 400 psi. Bumped plug w/1000 psi. Left well shut in. POB 7:00 PM 2-23-76.

2-25-76

Drilled to total depth of 702' (open hole 684-702'). Checked for fluid entry each foot below 696' - no entry until reaching 702'. Blew oil and some wtr from hole @ TD 702'. Pulled tbq and bit and ran 21 jts 2-3/8" OD 4.7# 8R EUE tbq, TE 673.07' set @ 672' GR.



RECEIVED

MAR 26 1976

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Agent

DATE

3-24-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side