Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPRO	OVED
Budget Bureau No.	1004-0135
Expires: March	31 1993

Bu	idget Bure	eau No.	1004-0	135
	Expires:	March	31, 1993	
	Decianat		Carial N	7.

		-api	· ·	*****	J.,	
	Lease	Desig	natio	n and	Serial	No.
•			,	_		9 11

6.	If	Indian.	Allottee	or	Tribe	Nam

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

TEMPIT — Tot such proposals	
IN TRIPLICATE	7. If Unit or CA, Agreement Designation
F-31-29N-17U escription) , N. 17 W.	NAVAYO TRACT 20 # 3 8. Well Name and No. 22-31 Navayor Trace 20 9. API Well No. 10. Field and Pool, or Exploratory Area Fajarito tenn D 11. County or Parish, State San Juna / Nml
s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
TYPE OF A	ACTION
Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Il pertinent details, and give pertinent dates, including estimated dates.	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
	IN TRIPLICATE F-31-29N-17U escription) A'. 17 W. S) TO INDICATE NATURE OF NOTICE, TYPE OF A Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Other

See arrach draginm



4. I hereby certify that		true and correct	ا ۸ نم	,	11.40 a.c. 0		(/111 10 /
Signed	Weil	being	plugged Tilley +	he	NMOCO	Date _	6/14/96
(This space for Fed	leral or State offic	ce use)				ACCEPTE	D FOR RECOND
Approved by Conditions of appro	oval, if anv:		Title			Date _	
Conditions of appro	,					JU.	N 1 4 1996

Elevations; 5210' KB=5196' GL. perforate @ 230'-50' below 135/8" csg shoe a circulate cmt to surface 17/2" hole -133/8" 42# 940 180'K.E (Gallup) Perfo 600', squeeze emf & displace to 400' - 180' K.B., 166' G.L. DAKOTA & MOTTISOF Perforate@ 1640', squeeze emt + displace -CAL. T. O.C. 2045 G.L. Shoe Plug for 95/8" perf@ 2595' squeeze & acolare cont to 2410' -121/4 hole -95/8%, 36 \$ set@ 2559 K.B Futindad Chirle P. U.H & perforate 51/2" @ 32245querze contoutside 51/2" & displace contiviside to 2608' 2545' G.L (DeChelly, Organ rock) P.U. H. perforate 51/2" @ 4800' squeeze ent autside 51/2" + displace ent inside to 4180' Hermosa. P.U.H to 6127 & perf 51/2" square cmt -outside 51/2" + displace cmt 1 pside to 6027" Cal. T.O.C 6756 6.E. DACAdox: Set ret. @ 1010', pump 100% excess:
Thru perfs, spotemt or top of
ret. to 6645' Packer set @ 9114 G.L-7128 K.B pecfs from 9189'-91' 4 9197- 9283'
2 Shots perft. (16 holes) Post-It™ brand fax transmittal memo 7671 # of pages : 834" hole -51/2", 15.5# set @ 7265' K.B 7251'G.L Dent. Phone 4