UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

	Budget Bureau No. 42-R1424
	5. LEASE SF-078739
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
ıt	7. UNIT AGREEMENT NAME San Juan 30-5 Unit
_	8. FARM OR LEASE NAME San Juan 30-5 Unit
	9. WELL NO. #51
	10. FIELD OR WILDCAT NAME
7	Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec 21, T30N, R5W 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico
	14. API NO. 30-039-22447
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6414' GR
EIVED I	

(Do not use this form for proposals to drill or to deepen or plug back to a difference reservoir. Use Form 9–331–C for such proposals.) gas well \Box other well 2. NAME OF OPERATOR Northwest Pipeline Corporation 3. ADDRESS OF OPERATOR P.O. BOX 90, Farmington, NM 87401

SUBSEQUENT REPORT OF:

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 below.) 1000' FNL & 1800' FEL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE SEP 2 1 (NOTE) Report re REPAIR WELL PULL OR ALTER CASING U. S. GEOLOCICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, an

Sept 15, 1980 -

Drilling

Spudded 12-1/4" Surface hole at 1800 hrs.

Sept 16, 1980

MULTIPLE COMPLETE

CHANGE ZONES ABANDON*

(other)

Ran 9 jts (348') of 9-5/8", 36#, K-55, ST&C set at 362'. Woodco cemented with 185 sacks Class "B" containing 1/4# gel flake per sx and 3% CaCl₂. Circulated out 5 bbls cement. displaced with 25 bbls and down at 0815 hrs. Hole size 8-3/4"

FARMINGTON, N. M.

Sept 17, 1980

Drilling with clear water and 8-3/4" bit.

Sept 18, 19, 1980

Drilling ahead.

Subsurface Safety Valve: Manu. and Type ___

ion or zone

18. I hereby certify that the for going is true and correct

_____ TITLE Production Clerk DATE

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

change of

CONFIDENTIAL See Instructions on Reverse Side