

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1860'S, 790'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 078580

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Howell C

9. WELL NO.
3A

10. FIELD OR WILDCAT NAME
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T-30-N, R-8-W
N.M.P.M.

12. COUNTY OR PARISH San Juan 13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6279' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-07-78: TD 3429'. Ran 89 jts. 7", 20#, K-55 intermediate casing, 3414' set at 3429'. Cemented w/393 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1825'.

12-14-78: TD 5690'. Ran 75 jts. 4 1/2", 10.5#, KS casing liner, 2430' set 3260-5690'. Float collar set at 5674'. Cemented w/424 cu. ft. cement. WOC 18 hours.

3-30-79: PBTD 5674'. Tested casing to 3500#, OK. Perfed Upper & Lower P.L. 5271, 5276, 5284, 5291, 5299, 5304, 5310, 5316, 5322, 5332, 5338, 5344, 5350, 5357, 5365, 5371, 5377, 5394, 5401, 5424, 5437, 5466, 5523, 5555, 5573, 5633, 5654' w/1 SPZ. Fraced w/84,000# 20/40 sand and 168,000 gal. water. Flushed w/6930 gal. water. Perfed C.H. & Men. 4596, 4683, 4724, 4803, 4814, 4821, 4828, 4859, 4878, 4886, 4894, 4902, 4910, 4950, 4982, 4990, 5010, 5044, 5052, 5060, 5078, 5086, 5094, 5111, 5179, 5186, 5194' w/1 SPZ. Fraced w/100,000# 20/40 sand and 200,000 gal. water. Flushed w/6600 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. G. Buices TITLE Drilling Clerk DATE April 2, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



nyyoc