## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: N192910

Page 1

## OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:PAYNE A 001E Meter #:93665 RTU:0-000-00 County:SAN JUAN

meter #:93665 RTU:0-00			RTU: 0-000-00	C	County:SAN JUAN		
<del></del>	NAME RES	ERVOIR OR P	POOL	TYPE PROD	METHOD PR	ROD MEDIUM PROD	
UPR COMP	PAYNE A O	O1E CHMV	02885	GAS	FLOW	TBG	
LWR COMP	PAYNE A O		93665 N.F.	GAS	FLOW	TBG	
		PRE	-FLOW SHUT-IN	PRESSURE DA	TA		
	Hour/Date	e Shut-In	Length of Tim	e Shut-In	SI Press.	PSIG   Stabilzed	
UPR COMP	09/26/93						
LWR COMP	09/3/6/93						
	l		FLOW TEST	DATE NO.1			
Comme	nced at (ho	our,date)*		T+A	Zone P	roducing (Upr/Lwr)	
TIME (hour, date)		LAPSED TIME PRI SINCE* Upper		ESSURE Lower	Prod Temp.	REMARKS	
09/26/93		Day 1		385		Both Zones SI	
09/27/93		Day 2	3/2	385		Both Zones SI	
09/23/93		Day 3	350	385		Both Zones SI	
09/29/93		Day 4	16000	365			
10/0//93		Day 5	160	365		07 <b>721</b> 9900 E	
10/0//93 Day Production rate during te			160 E	365		Carlotte Contract	
Oil: Gas: _	130	BOPD ba	ased on MFCPD:Tested tl ID-TEST SHUT-II	heu (Orific	e or Meter	Grav GOR	
UPR COMP	T		th of Time SI			abilized (yes/no)	
LWR COMP							

FLOW TEST NO. 2

PRESSURE

Zone producing (Upper or Lower):

(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	RIEMARKS
tion, and	- Cinos				
	<del> </del>				
,					
D 1					•
Production rate d	-				
Oil:	BOF	D based on	Bbls. in	Hours	Grav GOR
G25:		MCI	FPD: Tested thru	(Orifice or Meter	):
Kemarks:					
			<del></del>		
	har the informat	ion herein contais	ned is true and co	omplete to the be	st of my knowledge.
I hereby certify t					
	nct 2 1	1003		_	Ames Reduction Comes
Approved	OCT 2 1	1993	19 (	Operator	Amoco Production Compa
Approved	OCT 2 1	1993	19(	Operator	Amoio Goduction Compa usan Wiroda
Approved New Mexico C	OCT 2 1	1993	19 (	Operator	Amoro Goduction Compa isan Wiroda Ald Jechnologist

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at thour, date) \*\*

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aster District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOF (oil zones only).