

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM MAIL ROOM

Sundry Notices and Reports on Wells

36 FEB 23 AM 8:32

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1120' FSL, 1120' FEL, Sec.3, T-29-N, R-14-W, NMPM

5. Lease Number
SF-078110

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Locke #1

9. API Well No.
30-045-25630

10. Field and Pool
Basin Dakota

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

2-5-96 MIRU. ND WH. NU BOP. TOOH w/182 jts 2 3/8" tbq. SDON.
2-6-96 TIH w/4 1/2" gauge ring to 5700'. TOOH. TIH w/4 1/2" cmt retainer, set @ 5655'. PT tbq to 1500 psi, OK. Load hole & circ w/10 bbl wtr. PT csg to 500 psi/5 min, OK. Establish injection into Dakota perfs. Plug #1: pump 19 sx Class "B" cmt below cmt retainer into Dakota perfs, 12 sx Class "B" cmt above cmt retainer, TOC @ 5497'. TOOH. TIH, perf 3 sqz holes @ 4800'. Load hole w/10 bbl wtr. Attempt to establish injection. (Verbal approval to change plans from Marilyn Deaton, BLM). Perf 3 sqz holes @ 4750'. Load hole w/1 bbl wtr. Attempt to establish injection. TIH to 4868'. Plug #2: pump 17 sx Class "B" cmt inside csg @ 4644-4868'. TOOH to 2261'. Load hole w/5.5 bbl wtr. Plug #3: pump 12 sx Class "B" cmt inside csg @ 2103-2261'. TOOH to 1099'. Load hole w/3 bbl wtr. Plug #4: pump 44 sx Class "B" cmt inside csg @ 519-1099'. TOOH to 314'. Establish circ down csg & out bradenhead. Plug #5: pump 33 sx Class "B" cmt down csg & out bradenhead. Circ 2 bbl cmt to surface. TOOH. WOC. SDON.
2-7-96 ND BOP. Cut off WH. Fill 4 1/2" x 8 5/8" csg annulus w/20 sx Class "B" cmt. Install dry hole marker w/5 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 2-7-96.

14. I hereby certify that the foregoing is true and correct.

Signed *Deputy State Auditor* Title Regulatory Administrator Date 2/14/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

NMOC

APPROVED

[Signature]